

HC-STA-B24-HHFD-2TTM32-EL-AL - Housing



1079581

<https://www.phoenixcontact.com/us/products/1079581>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sleeve housing B24, for double locking latch, material: Die-cast aluminum, salt water resistant, cable outlets: 2, straight, 2x M32, height: 76 mm, cable gland: none, Standard

Your advantages

- Good shielding in the event of electromagnetic interference

Commercial data

Item number	1079581
Packing unit	1 pc
Minimum order quantity	50 pc
Note	Made to order (non-returnable)
Sales key	BF56
Product key	BF7APB
GTIN	4055626801056
Weight per piece (including packing)	22.22 g
Weight per piece (excluding packing)	264.3 g
Customs tariff number	85389099
Country of origin	PL

HC-STA-B24-HHFD-2TTM32-EL-AL - Housing



1079581

<https://www.phoenixcontact.com/us/products/1079581>

Technical data

Notes

General	for contact inserts HC-B24, BB46, D64, DD108, HV10/16, M
---------	--

Product properties

Type	B24
Product type	Housing with locking latch
Application	Standard
No. of cable outlets	2
Type of the screw connection	2x M32
Housing type	Sleeve housing
Cable outlet	straight
Pg screw connection	none

Dimensions

Width	44 mm
Height	76 mm
Length	120 mm

Material specifications

Housing surface material	uncoated
Housing material	Die-cast aluminum, salt water resistant

Mechanical properties

Mechanical data

Type of the screw connection	2x M32
Locking type	Pin

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP66
	IP67
Ambient temperature (operation)	-40 °C ... 125 °C

HC-STA-B24-HHFD-2TTM32-EL-AL - Housing



1079581

<https://www.phoenixcontact.com/us/products/1079581>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1079581>



EAC

Approval ID: RU C-DE.BL08.B.00511

HC-STA-B24-HHFD-2TTM32-EL-AL - Housing



1079581

<https://www.phoenixcontact.com/us/products/1079581>

Classifications

ECLASS

ECLASS-11.0	27440202
ECLASS-12.0	27440202
ECLASS-13.0	27440202

ETIM

ETIM 8.0	EC000437
----------	----------

UNSPSC

UNSPSC 21.0	31261500
-------------	----------

HC-STA-B24-HHFD-2TTM32-EL-AL - Housing



1079581

<https://www.phoenixcontact.com/us/products/1079581>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

1079581

<https://www.phoenixcontact.com/us/products/1079581>

Accessories

G-INS-M32-M68N-NNES-S - Cable gland

1411166

<https://www.phoenixcontact.com/us/products/1411166>



Cable gland, material for screw connection: Brass, nickel-plated, external cable diameter 15 mm ... 21 mm, shielding: no, connecting thread: M32 x 1.5, color: silver, with O-ring

G-INSEC-M32-M68N-NCRS-S - Cable gland

1411191

<https://www.phoenixcontact.com/us/products/1411191>



Cable gland, material for screw connection: Brass, nickel-plated, external cable diameter 14 mm ... 21 mm, shielding: yes, connecting thread: M32 x 1.5, color: silver, with O-ring

HC-STA-B24-HHFD-2TTM32-EL-AL - Housing



1079581

<https://www.phoenixcontact.com/us/products/1079581>

US-EMLP (20X9) CUS - Plastic label

0830085

<https://www.phoenixcontact.com/us/products/0830085>

Plastic label, can be ordered: by card, white, labeled according to customer specifications, mounting type: adhesive, lettering field size: 20 x 9 mm, Number of individual labels: 75



HC-B24-HCWD-PLR-BK - Protective cover

1346552

<https://www.phoenixcontact.com/us/products/1346552>

Protective cover B24, with double locking latch, protective cover material: PC, height: 25.4 mm, seal: yes



HC-STA-B24-HHFD-2TTM32-EL-AL - Housing



1079581

<https://www.phoenixcontact.com/us/products/1079581>

US-EMLP-HA (20X9) - Plastic label

0830989

<https://www.phoenixcontact.com/us/products/0830989>

Plastic label, Card, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: adhesive, lettering field size: 20 x 9 mm, Number of individual labels: 70



Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com