

1281251

https://www.phoenixcontact.com/us/products/1281251

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



CHARX connect professional, Repair kit, Accessories, with DC contact holder with integrated front part of the DC contacts, with replaceable mating face frame, with 5x M4X10 rounded head screws with Torx security drive, for replacement of the mating face frame of vehicle charging connectors, HPC CCS type 1, IEC 62196-3-1, SAE J1772, Screw mounting, housing: black, Replacement without draining the coolant

Product Description

Repair kit with replaceable mating face frame for CCS type 1 HPC DC vehicle connector

Your advantages

- · Complete product range
- · Developed and produced in accordance with the IATF 16949 automotive standard and ISO 9001
- · Maintenance-friendly replacement of the mating face frame without draining the coolant

Commercial Data

Item number	1281251
Packing unit	1 pc
Minimum order quantity	1 pc
Sales Key	EM01
Product Key	XWBAFB
GTIN	4063151478841
Weight per Piece (including packing)	263.5 g
Customs tariff number	85389099
Country of origin	DE



https://www.phoenixcontact.com/us/products/1281251



Technical Data

Notes

General	Replacement without draining the coolant
General	The vehicle connector housing does not have to be opened in order to replace the mating face frame.

Product properties

Product type	Repair kit
Product family	CHARX connect professional
Application	for replacement of the mating face frame of vehicle charging connectors
Туре	Accessories
Design	with DC contact holder with integrated front part of the DC contacts
	with replaceable mating face frame
	with 5x M4X10 rounded head screws with Torx security drive
Technology	Combined Charging System
	High Power Charging
Charging standard	HPC CCS type 1
Charging mode	Mode 4

Material specifications

Color (Housing)	black (9005)
Material (Housing)	Plastic

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-30 °C 50 °C
Ambient temperature (storage/transport)	-40 °C 80 °C

Standards and regulations

Standards

Standards/regulations	IEC 62196-3-1
	SAE J1772

Mounting

	Mounting type	Screw mounting




https://www.phoenixcontact.com/us/products/1281251



Drawings





Assembly drawing



1281251

https://www.phoenixcontact.com/us/products/1281251

Classifications

ECLASS

UNSPSC 21.0

ECLASS-11.0	27144792
ECLASS-12.0	27144792
ECLASS-13.0	27144792
ETIM	
ETIM 8.0	EC002884
UNSPSC	

39121500



1281251

https://www.phoenixcontact.com/us/products/1281251

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2023 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com