

XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Ground terminal, number of connections: 2, number of positions: 1, connection method: Push-X-connection, Rated cross section: 2.5 mm², cross section: 0.5 mm² - 4 mm², mounting type: NS 35/7,5, NS 35/15, color: green-yellow

Your advantages

- The compact design and front connection enable wiring in a confined space
- In addition to the testing option in the double function shaft, all terminal blocks provide an additional test pick-off
- Tested for railway applications

Commercial data

Item number	1343116
Packing unit	50 pc
Minimum order quantity	50 pc
Sales key	31BBE2
Product key	BE2521
GTIN	4063151652593
Weight per piece (including packing)	8.541 g
Weight per piece (excluding packing)	7.993 g
Customs tariff number	85369010
Country of origin	CN

XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>

Technical data

Product properties

Product type	Ground terminal block
Number of positions	1
Area of application	Railway industry
	Machine building
	Plant engineering
	Process industry
Number of connections	2
Number of rows	1

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Electrical properties

Rated surge voltage	8 kV
Maximum power dissipation for nominal condition	0.77 W

Connection data

Grounding foot	Yes
Number of connections per level	2
Nominal cross section	2.5 mm ²
Stripping length	10 mm ... 12 mm
Internal cylindrical gage	A3
Connection in acc. with standard	IEC 60947-7-2
Conductor cross section rigid	0.5 mm ² ... 4 mm ²
Cross section AWG	20 ... 12 (converted acc. to IEC)
Conductor cross section flexible	0.75 mm ² ... 4 mm ²
Conductor cross section, flexible [AWG]	18 ... 12 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve)	0.5 mm ² ... 2.5 mm ²
Flexible conductor cross section (ferrule with plastic sleeve)	0.5 mm ² ... 2.5 mm ²
Nominal cross section	2.5 mm ²

Dimensions

Width	5.2 mm
End cover width	2.2 mm
Height	48.6 mm
Depth	35.3 mm
Depth on NS 35/7,5	36.8 mm
Depth on NS 35/15	44.3 mm

Material specifications

XT 2,5-PE - Ground terminal



1343116

<https://www.phoenixcontact.com/no/products/1343116>

Color	green-yellow
Flammability rating according to UL 94	V0
Insulating material group	I
Insulating material	PA
Static insulating material application in cold	-60 °C
Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26	HL 1 - HL 3
Surface flammability NFPA 130 (ASTM E 162)	passed
Specific optical density of smoke NFPA 130 (ASTM E 662)	passed
Smoke gas toxicity NFPA 130 (SMP 800C)	passed

Mechanical properties

Mechanical data

Open side panel	Yes
-----------------	-----

Environmental and real-life conditions

Oscillation/broadband noise

Specification	DIN EN 50155 (VDE 0115-200):2022-06
Spectrum	Service life test category 1, class B, body mounted
Frequency	$f_1 = 5 \text{ Hz}$ to $f_2 = 150 \text{ Hz}$
ASD level	$0.964 \text{ (m/s}^2\text{)}^2\text{/Hz}$
Acceleration	0.58g
Test duration per axis	5 h
Test directions	X-, Y- and Z-axis
Result	Test passed

Shocks

Specification	DIN EN 50155 (VDE 0115-200):2022-06
Pulse shape	Half-sine
Acceleration	5g
Shock duration	30 ms
Number of shocks per direction	3
Test directions	X-, Y- and Z-axis (pos. and neg.)
Result	Test passed

Ambient conditions

Ambient temperature (operation)	-60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C

XT 2,5-PE - Ground terminal



1343116

<https://www.phoenixcontact.com/no/products/1343116>

Permissible humidity (operation)	20 % ... 90 %
Permissible humidity (storage/transport)	30 % ... 70 %

Standards and regulations

Connection in acc. with standard	IEC 60947-7-2
----------------------------------	---------------

Mounting

Mounting type	NS 35/7,5
	NS 35/15

XT 2,5-PE - Ground terminal


1343116

<https://www.phoenixcontact.com/no/products/1343116>



Drawings

Circuit diagram



XT 2,5-PE - Ground terminal



1343116

<https://www.phoenixcontact.com/no/products/1343116>

Classifications

ECLASS

ECLASS-11.0	27141141
ECLASS-13.0	27250103

ETIM

ETIM 9.0	EC000901
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



Accessories

FBS 2-5 - Plug-in bridge

3030161

<https://www.phoenixcontact.com/no/products/3030161>



Plug-in bridge, pitch: 5.2 mm, number of positions: 2, length: 23 mm, color: red

FBS 3-5 - Plug-in bridge

3030174

<https://www.phoenixcontact.com/no/products/3030174>



Plug-in bridge, pitch: 5.2 mm, number of positions: 3, length: 23 mm, color: red

XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



FBS 4-5 - Plug-in bridge

3030187

<https://www.phoenixcontact.com/no/products/3030187>



Plug-in bridge, pitch: 5.2 mm, number of positions: 4, length: 23 mm, color: red

FBS 5-5 - Plug-in bridge

3030190

<https://www.phoenixcontact.com/no/products/3030190>



Plug-in bridge, pitch: 5.2 mm, number of positions: 5, length: 23 mm, color: red

XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



FBS 10-5 - Plug-in bridge

3030213

<https://www.phoenixcontact.com/no/products/3030213>



Plug-in bridge, pitch: 5.2 mm, number of positions: 10, length: 23 mm, color: red

FBS 20-5 - Plug-in bridge

3030226

<https://www.phoenixcontact.com/no/products/3030226>



Plug-in bridge, pitch: 5.2 mm, number of positions: 20, color: red

XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



FBS 50-5 - Plug-in bridge

3038930

<https://www.phoenixcontact.com/no/products/3038930>



Plug-in bridge, pitch: 5.2 mm, number of positions: 50, color: red

FBSR 2-5 - Plug-in bridge

3033702

<https://www.phoenixcontact.com/no/products/3033702>



Plug-in bridge, pitch: 5.2 mm, number of positions: 2, color: red

XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



FBSR 3-5 - Plug-in bridge

3001591

<https://www.phoenixcontact.com/no/products/3001591>



Plug-in bridge, pitch: 5.2 mm, number of positions: 3, color: red

FBSR 4-5 - Plug-in bridge

3001592

<https://www.phoenixcontact.com/no/products/3001592>



Plug-in bridge, pitch: 5.2 mm, number of positions: 4, color: red

XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



FBSR 5-5 - Plug-in bridge

3001593

<https://www.phoenixcontact.com/no/products/3001593>

Plug-in bridge, pitch: 5.2 mm, number of positions: 5, color: red



FBSR 10-5 - Plug-in bridge

3033710

<https://www.phoenixcontact.com/no/products/3033710>

Plug-in bridge, pitch: 5.2 mm, number of positions: 10, color: red



XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



FBS 2-5 BU - Plug-in bridge

3036877

<https://www.phoenixcontact.com/no/products/3036877>



Plug-in bridge, pitch: 5.2 mm, number of positions: 2, color: blue

FBS 3-5 BU - Plug-in bridge

3036880

<https://www.phoenixcontact.com/no/products/3036880>



Plug-in bridge, pitch: 5.2 mm, number of positions: 3, color: blue

XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



FBS 4-5 BU - Plug-in bridge

3036893

<https://www.phoenixcontact.com/no/products/3036893>

Plug-in bridge, pitch: 5.2 mm, number of positions: 4, color: blue



FBS 5-5 BU - Plug-in bridge

3036903

<https://www.phoenixcontact.com/no/products/3036903>

Plug-in bridge, pitch: 5.2 mm, number of positions: 5, color: blue



XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



FBS 10-5 BU - Plug-in bridge

3036916

<https://www.phoenixcontact.com/no/products/3036916>



Plug-in bridge, pitch: 5.2 mm, number of positions: 10, color: blue

FBS 20-5 BU - Plug-in bridge

3036929

<https://www.phoenixcontact.com/no/products/3036929>



Plug-in bridge, pitch: 5.2 mm, number of positions: 20, color: blue

XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



FBS 50-5 BU - Plug-in bridge

3032114

<https://www.phoenixcontact.com/no/products/3032114>



Plug-in bridge, pitch: 5.2 mm, number of positions: 50, color: blue

D-ST 2,5 - End cover

3030417

<https://www.phoenixcontact.com/no/products/3030417>



End cover, depth: 29.1 mm, width: 2.2 mm, height: 48.6 mm, color: gray

XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



D-ST 2,5-0,8 OG - End cover

3030511

<https://www.phoenixcontact.com/no/products/3030511>

End cover, depth: 29 mm, width: 0.8 mm, height: 48.6 mm, color: orange



ATP-ST 4 - Partition plate

3030721

<https://www.phoenixcontact.com/no/products/3030721>

Partition plate, depth: 39 mm, width: 2 mm, height: 59.8 mm, color: gray



XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



DS-ST 2,5 - Cover segment

3036602

<https://www.phoenixcontact.com/no/products/3036602>



End cover segments, large segment: 32.25 x 13.83 x 0.9, small segment: 22.65 x 11.65 x 0.9, color: gray

WS PT 2,5 - Warning label

1029026

<https://www.phoenixcontact.com/no/products/1029026>



Warning label, yellow/black, labeled: Lightning flash, mounting type: plug in, for terminal block width: 5.2 mm

XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



WS-DIO PT 2,5 - Warning label

1029037

<https://www.phoenixcontact.com/no/products/1029037>



Warning label, yellow/black, labeled: Diode, mounting type: plug in, for terminal block width: 5.2 mm

NS 35/ 7,5 PERF 2000MM - DIN rail perforated

0801733

<https://www.phoenixcontact.com/no/products/0801733>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



NS 35/ 7,5 UNPERF 2000MM - DIN rail, unperforated

0801681

<https://www.phoenixcontact.com/no/products/0801681>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

NS 35/ 7,5 WH PERF 2000MM - DIN rail perforated

1204119

<https://www.phoenixcontact.com/no/products/1204119>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



NS 35/ 7,5 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204122

<https://www.phoenixcontact.com/no/products/1204122>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

NS 35/ 7,5 AL UNPERF 2000MM - DIN rail, unperforated

0801704

<https://www.phoenixcontact.com/no/products/0801704>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver

XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



NS 35/ 7,5 ZN PERF 2000MM - DIN rail perforated

1206421

<https://www.phoenixcontact.com/no/products/1206421>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver

NS 35/ 7,5 ZN UNPERF 2000MM - DIN rail, unperforated

1206434

<https://www.phoenixcontact.com/no/products/1206434>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver

XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



NS 35/ 7,5 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

0801762

<https://www.phoenixcontact.com/no/products/0801762>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

NS 35/ 7,5 CAP - End cap

1206560

<https://www.phoenixcontact.com/no/products/1206560>

DIN rail end piece, for DIN rail NS 35/7.5



XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>

NS 35/15 PERF 2000MM - DIN rail perforated

1201730

<https://www.phoenixcontact.com/no/products/1201730>




DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

NS 35/15 UNPERF 2000MM - DIN rail, unperforated

1201714

<https://www.phoenixcontact.com/no/products/1201714>



DIN rail, unperforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



NS 35/15 WH PERF 2000MM - DIN rail perforated

0806602

<https://www.phoenixcontact.com/no/products/0806602>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: white

NS 35/15 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204135

<https://www.phoenixcontact.com/no/products/1204135>



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



NS 35/15 AL UNPERF 2000MM - DIN rail, unperforated

1201756

<https://www.phoenixcontact.com/no/products/1201756>



DIN rail, unperforated, similar to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver

NS 35/15 ZN PERF 2000MM - DIN rail perforated

1206599

<https://www.phoenixcontact.com/no/products/1206599>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, Standard profile, color: silver

XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



NS 35/15 ZN UNPERF 2000MM - DIN rail, unperforated

1206586

<https://www.phoenixcontact.com/no/products/1206586>



DIN rail, unperforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, Standard profile, color: silver

NS 35/15 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201895

<https://www.phoenixcontact.com/no/products/1201895>



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



NS 35/15 CAP - End cap

1206573

<https://www.phoenixcontact.com/no/products/1206573>

DIN rail end piece, for DIN rail NS 35/15



NS 35/15-2,3 UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201798

<https://www.phoenixcontact.com/no/products/1201798>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile 2.3 mm, color: silver

XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



ZB 5 :UNBEDRUCKT - Zack marker strip

1050004

<https://www.phoenixcontact.com/no/products/1050004>



Zack marker strip, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 5.2 mm, lettering field size: 5.1 x 10.5 mm, Number of individual labels: 10

ZB 5 CUS - Zack marker strip

0824962

<https://www.phoenixcontact.com/no/products/0824962>



Zack marker strip, can be ordered: Strip, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 5.2 mm, lettering field size: 5.15 x 10.5 mm, Number of individual labels: 10

XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



ZB 5,LGS:FORTL.ZAHLEN - Zack marker strip

1050017

<https://www.phoenixcontact.com/no/products/1050017>



Zack marker strip, Strip, white, labeled, printed horizontally: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 491 ... 500, mounting type: snapped, for terminal block width: 5.2 mm, lettering field size: 5.15 x 10.5 mm, Number of individual labels: 10

ZB 5,QR:FORTL.ZAHLEN - Zack marker strip

1050020

<https://www.phoenixcontact.com/no/products/1050020>



Zack marker strip, white, Printed vertically: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 491 ... 500, mounting type: snapped, for terminal block width: 5.2 mm, lettering field size: 5.15 x 10.5 mm

XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



ZB 5,LGS:GLEICHE ZAHLEN - Zack marker strip

1050033

<https://www.phoenixcontact.com/no/products/1050033>



Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, printed horizontally: Identical numbers 1 or 2, etc. up to 100, mounting type: snapped, for terminal block width: 5.2 mm, lettering field size: 5.15 x 10.5 mm, Number of individual labels: 10

ZB 5,LGS:L1-N,PE - Zack marker strip

1050415

<https://www.phoenixcontact.com/no/products/1050415>



Zack marker strip, Strip, white, labeled, horizontal: L1, L2, L3, N, PE, L1, L2, L3, N, PE, mounting type: snapped, for terminal block width: 5.2 mm, lettering field size: 5.15 x 10.5 mm, Number of individual labels: 10

XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



UC-TM 5 - Marker for terminal blocks

0818108

<https://www.phoenixcontact.com/no/products/0818108>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 5.2 mm, lettering field size: 4.6 x 10.5 mm, Number of individual labels: 96

UC-TM 5 CUS - Marker for terminal blocks

0824581

<https://www.phoenixcontact.com/no/products/0824581>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 5.2 mm, lettering field size: 10.5 x 4.6 mm, Number of individual labels: 96

XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



UCT-TM 5 - Marker for terminal blocks

0828734

<https://www.phoenixcontact.com/no/products/0828734>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, for terminal block width: 5.2 mm, lettering field size: 4.6 x 10.5 mm, Number of individual labels: 72

UCT-TM 5 CUS - Marker for terminal blocks

0829595

<https://www.phoenixcontact.com/no/products/0829595>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 5.2 mm, lettering field size: 4.6 x 10.5 mm, Number of individual labels: 72

XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>

GBS 5-25X12 - Group marker label for terminal marking

0810588

<https://www.phoenixcontact.com/no/products/0810588>



Group marker label, snaps onto terminal center for screw, spring-cage and quick connection terminal blocks, labeled with a 25 x 12 mm label or manually with the B-STIFT, in the foot part with ZB 5

GBS 5-25X5 - Group marker label for terminal marking

0829126

<https://www.phoenixcontact.com/no/products/0829126>



Group marking label, can be snapped into terminal center for screw, spring-cage, push-in, and fast connection terminal blocks, can be labeled with a 24 x 4 mm label or manually using B-STIFT, in the foot part with ZB 5

XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



STP 5-2-ZB - Marker carriers

3037643

<https://www.phoenixcontact.com/no/products/3037643>



Marker carriers, snaps into ST 2,5 spring-cage terminal blocks, can be marked with UC-TM 5, UC-TMF 5, UCT-TM 5, UCT-TMF 5, ZB 5, or ZBF 5, gray, unlabeled, mounting type: snapped

ZBF 5:UNBEDRUCKT - Zack Marker strip, flat

0808642

<https://www.phoenixcontact.com/no/products/0808642>



Zack Marker strip, flat, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 5 mm, lettering field size: 5.1 x 5.2 mm, Number of individual labels: 10

XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



ZBF 5 CUS - Zack Marker strip, flat

0825025

<https://www.phoenixcontact.com/no/products/0825025>



Zack Marker strip, flat, can be ordered: Strip, white, labeled according to customer specifications, mounting type: snap into flat marker groove, for terminal block width: 5 mm, lettering field size: 5.15 x 5.15 mm, Number of individual labels: 10

ZBF 5,LGS:FORTL.ZAHLEN - Zack Marker strip, flat

0808671

<https://www.phoenixcontact.com/no/products/0808671>



Zack Marker strip, flat, Strip, white, labeled, printed horizontally: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 491 ... 500, mounting type: snapped, for terminal block width: 5 mm, lettering field size: 5.15 x 5.15 mm, Number of individual labels: 10

XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



ZBF 5,QR:FORTL.ZAHLEN - Zack Marker strip, flat

0808697

<https://www.phoenixcontact.com/no/products/0808697>



Zack Marker strip, flat, Strip, white, labeled, Printed vertically: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 91 ... 100, mounting type: snapped, for terminal block width: 5 mm, lettering field size: 5.15 x 5.15 mm, Number of individual labels: 10

ZBF 5,LGS:GERADE ZAHLEN - Zack Marker strip, flat

0810821

<https://www.phoenixcontact.com/no/products/0810821>



Zack Marker strip, flat, Strip, white, labeled, printed horizontally: consecutive even numbers 2 ... 20, 22 ... 40, etc. up to 82 ... 100, mounting type: snapped, for terminal block width: 5 mm, lettering field size: 5.15 x 5.15 mm, Number of individual labels: 10

XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



ZBF 5,LGS:UNGERADE ZAHLEN - Zack Marker strip, flat

0810863

<https://www.phoenixcontact.com/no/products/0810863>




Zack Marker strip, flat, Strip, white, labeled, printed horizontally: Odd numbers 1 - 19, 21 - 39, etc. up to 81 - 99, mounting type: snapped, for terminal block width: 5 mm, lettering field size: 5.15 x 5.15 mm, Number of individual labels: 10

UC-TMF 5 - Marker for terminal blocks

0818153

<https://www.phoenixcontact.com/no/products/0818153>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 5.2 mm, lettering field size: 4.6 x 5.1 mm, Number of individual labels: 96

XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



UC-TMF 5 CUS - Marker for terminal blocks

0824638

<https://www.phoenixcontact.com/no/products/0824638>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into flat marker groove, for terminal block width: 5.2 mm, lettering field size: 4.6 x 5.1 mm, Number of individual labels: 96

UCT-TMF 5 - Marker for terminal blocks

0828744

<https://www.phoenixcontact.com/no/products/0828744>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, for terminal block width: 5.2 mm, lettering field size: 4.4 x 4.7 mm, Number of individual labels: 72

XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



UCT-TMF 5 CUS - Marker for terminal blocks

0829658

<https://www.phoenixcontact.com/no/products/0829658>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into flat marker groove, for terminal block width: 5.2 mm, lettering field size: 4.4 x 4.7 mm, Number of individual labels: 72

MPS-MT - Test plug

0201744

<https://www.phoenixcontact.com/no/products/0201744>



Test plug, with solder connection up to 1 mm² conductor cross section, number of positions: 1, color: gray

XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



MPS-IH WH - Insulating sleeve

0201663

<https://www.phoenixcontact.com/no/products/0201663>

Insulating sleeve, color: white



MPS-IH RD - Insulating sleeve

0201676

<https://www.phoenixcontact.com/no/products/0201676>

Insulating sleeve, color: red



XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>




MPS-IH BU - Insulating sleeve

0201689

<https://www.phoenixcontact.com/no/products/0201689>

Insulating sleeve, color: blue



MPS-IH YE - Insulating sleeve

0201692

<https://www.phoenixcontact.com/no/products/0201692>

Insulating sleeve, color: yellow



XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



MPS-IH GN - Insulating sleeve

0201702

<https://www.phoenixcontact.com/no/products/0201702>

Insulating sleeve, color: green



MPS-IH GY - Insulating sleeve

0201728

<https://www.phoenixcontact.com/no/products/0201728>

Insulating sleeve, color: gray



XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



MPS-IH BK - Insulating sleeve

0201731

<https://www.phoenixcontact.com/no/products/0201731>

Insulating sleeve, color: black



ISH 2,5/0,2 - Insulating sleeve

3002843

<https://www.phoenixcontact.com/no/products/3002843>

Insulating sleeve, color: white



XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



ISH 2,5/0,5 - Insulating sleeve

3002856

<https://www.phoenixcontact.com/no/products/3002856>



Insulating sleeve, color: gray

ISH 2,5/1,0 - Insulating sleeve

3002869

<https://www.phoenixcontact.com/no/products/3002869>



Insulating sleeve, color: black

XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



PAI-4-FIX-5/6 BU - Test adapter

3035975

<https://www.phoenixcontact.com/no/products/3035975>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

PAI-4-FIX-5/6 OG - Test adapter

3035974

<https://www.phoenixcontact.com/no/products/3035974>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



PAI-4-FIX-5/6 YE - Test adapter

3035977

<https://www.phoenixcontact.com/no/products/3035977>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

PAI-4-FIX-5/6 RD - Test adapter

3035976

<https://www.phoenixcontact.com/no/products/3035976>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



PAI-4-FIX-5/6 GN - Test adapter

3035978

<https://www.phoenixcontact.com/no/products/3035978>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

PAI-4-FIX-5/6 BK - Test adapter

3035980

<https://www.phoenixcontact.com/no/products/3035980>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



PAI-4-FIX-5/6 GY - Test adapter

3035982

<https://www.phoenixcontact.com/no/products/3035982>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

PAI-4-FIX-5/6 VT - Test adapter

3035979

<https://www.phoenixcontact.com/no/products/3035979>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



PAI-4-FIX-5/6 BN - Test adapter

3035981

<https://www.phoenixcontact.com/no/products/3035981>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

PAI-4-FIX-5/6 WH - Test adapter

3035983

<https://www.phoenixcontact.com/no/products/3035983>



4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



PS-5 - Test plug

3030983

<https://www.phoenixcontact.com/no/products/3030983>



Test plug, Modular test plug, number of positions: 1, color: red

DP PS-5 - Spacer plate

3036725

<https://www.phoenixcontact.com/no/products/3036725>



Spacer plate, depth: 29 mm, width: 5.2 mm, height: 22.4 mm, number of positions: 1, color: red

XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



PS-5/2,3MM RD - Test plug

3038723

<https://www.phoenixcontact.com/no/products/3038723>



Test plug, number of positions: 1, color: red

ST-BW 0 - Actuation tool

1200135

<https://www.phoenixcontact.com/no/products/1200135>



Actuation tool, for all 1.5 mm² spring cages from PT 1,5/S and FT 1,5/S

XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



SZS 0,4X2,5 VDE - Screwdriver

1205037

<https://www.phoenixcontact.com/no/products/1205037>



Screwdriver, slot-headed, VDE insulated, size: 0.4 x 2.5 x 80 mm, 2-component grip, with non-slip grip

SF-SL 0,6X3,5-100 S-VDE - Screwdriver

1212587

<https://www.phoenixcontact.com/no/products/1212587>



Actuation tool, for ST terminal blocks, VDE insulated, with slimmer insulation integrated in the blade, also suitable for use as a bladed screwdriver, size: 0.6 x 3.5 x 100 mm, 2-component grip, with non-slip grip

XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



SZK PZ0 VDE - Screwdriver

1206447

<https://www.phoenixcontact.com/no/products/1206447>



Screwdriver, PZ crosshead, VDE insulated, size: PZ 0 x 80 mm, 2-component grip, with non-slip grip

AI 0,34- 8 TQ - Ferrule

3203066

<https://www.phoenixcontact.com/no/products/3203066>



Ferrule, sleeve length: 8 mm, color: turquoise

XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



AI 0,5 - 8 WH - Ferrule

3200014

<https://www.phoenixcontact.com/no/products/3200014>



Ferrule, sleeve length: 8 mm, color: white

AI 0,75- 8 GY - Ferrule

3200519

<https://www.phoenixcontact.com/no/products/3200519>



Ferrule, sleeve length: 8 mm, color: gray

XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



AI 0,34-10 TQ - Ferrule

3241129

<https://www.phoenixcontact.com/no/products/3241129>



Ferrule, sleeve length: 10 mm, color: turquoise

AI 0,5 -10 WH - Ferrule

3201275

<https://www.phoenixcontact.com/no/products/3201275>



Ferrule, sleeve length: 10 mm, color: white

XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



AI 0,75-10 GY - Ferrule

3201288

<https://www.phoenixcontact.com/no/products/3201288>



Ferrule, sleeve length: 10 mm, color: gray

AI 1 -10 RD - Ferrule

3200182

<https://www.phoenixcontact.com/no/products/3200182>



Ferrule, sleeve length: 10 mm, color: red

XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



AI 1,5 -10 BK - Ferrule

3200195

<https://www.phoenixcontact.com/no/products/3200195>



Ferrule, sleeve length: 10 mm, color: black

AI 2,5 -10 BU - Ferrule

3202533

<https://www.phoenixcontact.com/no/products/3202533>



Ferrule, sleeve length: 10 mm, color: blue

XT 2,5-PE - Ground terminal

1343116

<https://www.phoenixcontact.com/no/products/1343116>



PROJECT COMPLETE - Software

1050453

<https://www.phoenixcontact.com/no/products/1050453>



Intuitive planning and marking software for configuring terminal strips and for professional marking of marking materials for terminal blocks, conductors, cables, devices, and systems. The software is available for download

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT AS

Strømsveien 344

N-1081 Oslo

+47 22 07 68 00

norge@phoenixcontact.com