

1854051

https://www.phoenixcontact.com/us/products/1854051

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Half screw connection Pg21, made of metal, consisting of rubber seal with one hole and one pressure screw, for type 2 - 4 housings, cable [mm] 17 - 20.5

Commercial Data

Item number	1854051
Packing unit	1 pc
Minimum order quantity	5 pc
Sales Key	AB01
Product Key	ABLAZA
Catalog Page	Page 45 (C-2-2013)
GTIN	4017918145774
Weight per Piece (including packing)	26.36 g
Weight per Piece (excluding packing)	26.36 g
Customs tariff number	74153300
Country of origin	PL



1854051

https://www.phoenixcontact.com/us/products/1854051

Technical Data

Notes

Safety note

Safety note

WARNING: The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property.

- WARNING: Commission properly functioning products only.
 The products must be regularly inspected for damage.
 Decommission defective products immediately. Replace damaged products. Repairs are not possible.
- WARNING: Only electrically qualified personnel may install and operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics of electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicates that only personnel familiar with electrical engineering are allowed to install and operate the product.
- The products are suitable for applications in plant, controller, and electrical device engineering.
- When operating the connectors in outdoor applications, they must be separately protected against environmental influences.
- Assembled products may not be manipulated or improperly opened.
- Only use mating connectors that are specified in the technical data of the standards listed (e.g. the ones listed in the product accessories online at phoenixcontact.com/products).
- When using the product in direct connection with third-party manufacturers, the user is responsible.
- For operating voltages > 50 V AC, conductive connector housings must be grounded
- Ensure that the protective or functional ground has been properly connected.
- VDE 0100/1.97 § 411.1.3.2 and DIN EN 60 204/11.98 § 14.1.3 are applicable when combining several circuits in a cable and/or connector
- Observe the corresponding technical data. You will find information:
- o On the product
- o On the packing label
- o In the supplied documentation
- o Online at phoenixcontact.com/products under the product
- Only use tools recommended by Phoenix Contact
- The installation notes/Design In documents online on the download page at phoenixcontact.com/products must be observed for this product.
- Use a protective cap to protect connectors that are not in use. The suitable accessories are available online in the accessory section of the product at phoenixcontact.com/products
- Operate the connector only when it is fully plugged in.
- Ensure that when laying the cable, the tensile load on the connectors does not exceed the upper limit specified in the



1854051

https://www.phoenixcontact.com/us/products/1854051

Ambient temperature (operation)

	standards.
	 Observe the minimum bending radius of the cable. Lay the cable without twisting it.
	 The connector warms up in normal operation. Depending on the ambient conditions, the surface of the connector can continue to warm up. In this case, the user is responsible for posting warnings (e.g. DIN EN ISO 13732-1:2008-12).
Product properties	
Product type	Half screw connection
Product family	VARIOCON
No. of conductors	1
Shielded	no
Dimensions	
Width	33.5 mm
Height	33.5 mm
Length	30 mm
Wrench size, union nut	30 mm
Thread type on seal side	Pg21
Naterial specifications	
Seal material	TPE
Material (GRP)	TPE (Seal)
	Brass (Screw connection)
Cable/line	
External cable diameter	17 mm 20.5 mm
	17 mm 20.5 mm
Tightening torque, union nut	10.00 Nm
Environmental and real-life conditions	
Ambient conditions	
Degree of protection	IP67

-40 °C ... 125 °C



1854051

https://www.phoenixcontact.com/us/products/1854051

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/1854051



EAC

Approval ID: B.01687



1854051

https://www.phoenixcontact.com/us/products/1854051

Classifications

UNSPSC 21.0

ECLASS

ECLASS-11.0	27144432
ECLASS-12.0	27140801
ECLASS-13.0	27140801
ETIM	
ETIM 8.0	EC000441
UNSPSC	

39121300



1854051

https://www.phoenixcontact.com/us/products/1854051

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values



1854051

https://www.phoenixcontact.com/us/products/1854051

Accessories

VC-M-KV-PG21- 0 - Half screw connection

1854983

https://www.phoenixcontact.com/us/products/1854983



Half screw connection made of metal with rubber seal without hole for sealing or for individual holes

Phoenix Contact 2023 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com