

UPS-BAT/VRLA/ 24DC/ 7.2AH


Order No.: 2320319



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2320319>

Rechargeable battery module, lead AGM, VRLA technology, 24 V DC, 7.2 Ah, tool-free battery replacement.



Commercial data	
GTIN (EAN)	 4 046356 553353
sales group	H061
Pack	1 pcs.
Catalog page information	Page 619 (IF-2011)

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data	
Input data	
Nominal input voltage	24 V DC
Buffer period	10 min (20 A)
	3 min (40 A)
Output data	
Output current	max. 50 A
Connection in parallel	15
Connection in series	No
Output fuse	2x 25 A

General data

Disposal	Used batteries must not be thrown away with household waste, they should instead be disposed of in accordance with applicable national regulations. They can also be returned to Phoenix Contact or the manufacturer.
Width	135 mm
Height	202 mm
Depth	110 mm
Net weight	5.9 kg
Memory medium	battery 7.2 Ah
Degree of protection	IP20
Protection class	III
Ambient temperature (operation)	0 °C ... 40 °C
Ambient temperature (storage/transport)	0 °C ... 40 °C
Max. permissible relative humidity (operation)	≤ 95 %
Mounting position	horizontal DIN rail NS 35, EN 60715
Standard - Electrical safety	EN 60950-1/VDE 0805 (SELV) EN 61558-2-17
Standard – Electronic equipment for use in electrical power installations and their assembly into electrical power installations	EN 50178/VDE 0160 (PELV)
UL approvals	UL/C-UL listed UL 508 UL/C-UL Recognized UL 60950 UL/C-UL Listed UL 1604 Class I, Division 2, Groups A, B, C, D UL listed ANSI/ISA-12.12.01 class I, division 2, groups A, B, C, D UL/C-UL Recognized UL 1778
VdS approval	G 193046

Certificates / Approvals

Certification	CUL
Certifications applied for:	UL Listed / CUL Listed / UL / UL-EX

Accessories


Item	Designation	Description
Fuse		
0913757	SI FORM C 25 A DIN 72581	Flat-type plug-in fuse, type C, color code: white, nominal current: 25 A

General

2866857	QUINT-ADAPTER/4	Assembly adapter for QUINT-BAT/24DC... on 35mm rail
---------	-----------------	---

Diagrams/Drawings

Block diagram



Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;