

## Industrial Ethernet Switch - FL SWITCH GHS 12G/8-L3 - 2700787

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

Ethernet Gigabit Modular Switch with eight 10/100/1000 Mbps RJ45 slots and four 1000 Mbps SFP ports, can be extended by up to 28 ports, with integrated routing function



Gigabit Modular Switch with integrated routing function

### Product description

The Gigabit Modular Switch is a high-performance managed switch, which covers the port requirements of industrial applications in a modular and flexible way. It also supports all popular Gigabit and Fast Ethernet transmission standards, IT standard protocols, and the PROFINET and EtherNet/IP™ automation protocols.

For use in the production backbone, the FL SWITCH GHS 12G/8 is the first switch, which has integrated 12 Gigabit ports and also supports the accommodation of interface modules for up to 16 additional 100 Mbps ports. With the integrated Layer 3 license, the switch can be configured as a router. The GHS switch can provide routing in up to 28 different subnetworks. With VRRP (Virtual Redundancy Routing Protocol) it can also be operated as a redundant router.

### Product Features

- ✓ Connection of connection media that can be assembled in the field, such as POF, HCS, and GI HCS
- ✓ Quick and easy local configuration options with the new operator/display interface
- ✓ Security in the automation network according to IEEE 802.1X
- ✓ Connection of Gigabit fiberglass via FL SFP plug-in modules
- ✓ Integrated routing function



### Key commercial data

Packing unit	1 pc
Custom tariff number	85176200
Country of origin	Germany

### Technical data

#### Note:

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

# Industrial Ethernet Switch - FL SWITCH GHS 12G/8-L3 - 2700787

## Technical data

### Dimensions

Width	287 mm
Height	125 mm
Depth	115 mm

### Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-20 °C ... 55 °C (non-condensing)
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Permissible humidity (operation)	10 % ... 95 % (non-condensing)
Permissible humidity (storage/transport)	10 % ... 95 % (non-condensing)
Air pressure (operation)	80 kPa ... 108 kPa (2000 above sea level)
Air pressure (storage/transport)	66 kPa ... 108 kPa (3500 m above sea level)
Noise immunity	EN 61000-6-2:2005

### SFP interface

Interface	Ethernet (SFP)
No. of ports	4 (SFP ports)
Transmission speed	1000 MBit/s (full duplex)
Transmission physics	FO

### Copper interface

Interface	Ethernet (RJ45)
No. of ports	8
Transmission speed	10/100/1000 MBit/s
Connection method	RJ45
Note on connection method	Auto negotiation and autocrossing
Transmission physics	Copper

### Interface expansion

Interface	Ethernet
No. of ports	2 (Per interface module)
Connection method	via interface module
Note on connection method	Max. 4 interface modules (without extension)
Transmission speed	10/100 MBit/s (full duplex)
Transmission physics	Multimode fiberglass
	Single mode fiberglass
	POF-SCRJ
	GI-HCS fibers
	Copper

# Industrial Ethernet Switch - FL SWITCH GHS 12G/8-L3 - 2700787

## Technical data

### Interface expansion

	PoE
--	-----

### Function

Basic functions	Store-and-forward switch, smart mode, port mirroring, multicast filtering, IGMP snooping, VLAN, Media Redundancy Protocol (MRP according to IEC 62439), Rapid Spanning Tree (RSTP), Fast Ring Detection (FRD), Large Tree Support, IEEE 802.1X security, port security, PROFINET IO device, GMRP, GVRP, SNTP, 2 digital inputs
Supported browsers	Internet Explorer 5.5 or higher
PROFINET IO device function	PROFINET device
PROFINET IO specification	Version 1.1
Status and diagnostic indicators	Large operator display (contains IP address and other parameters), 2 status LEDs per Ethernet port: LINK and selection of Status Activity, 100, full duplex, supply voltage $U_{S1}$ and $U_{S2}$ (redundant supply voltage), and FAIL

### Network expansion parameters

Maximum conductor length ((twisted pair)	100 m
--	-------

### Supply voltage

Supply voltage	24 V DC
Residual ripple	3.6 V <sub>PP</sub> (within the permitted voltage range)
Supply voltage range	18.5 V DC ... 30.2 V DC
Typical current consumption	800 mA (Up to 2.7 A, depends on the configuration)
Max. current consumption	2.7 A

### General

Mounting type	DIN rail
Type AX	Stand-alone
Weight	2700 g
Material base plate	Die-cast aluminum, corrosion-resistant
Noise emission	EN 61000-6-3/-4

### Mechanical tests

Type of test	Shock in acc. with EN 60068-2-27/IEC 60068-2-27
Test result	Operation: 25 g, 11 ms duration, semi-sinusoidal shock impulse
Type of test	Shock in acc. with EN 60068-2-27/IEC 60068-2-27
Test result	Storage/Transport: 50 g, 11 ms duration, semi-sinusoidal shock impulse
Type of test	Vibration resistance in acc. with EN 60068-2-6/IEC 60068-2-6
Test result	Operation/Storage/Transport: 5 g, 150 Hz, Criterion 3
Type of test	Free fall in acc. with IEC 60068-2-32
Test result	1 m

# Industrial Ethernet Switch - FL SWITCH GHS 12G/8-L3 - 2700787

## Technical data

### Conformity with EMC directives

Test standard	IEC 61000-4-2 (ESD)
Test result	Criterion B, Class 3
Test standard	IEC 61000-4-3 (immunity to radiated interference)
Test result	Criterion A, 10 V/m
Test standard	IEC 61000-4-4 (burst)
Test result	Criterion A, 1 kV
Test standard	IEC 61000-4-5 (surge)
Test result	Criterion B
Test standard	IEC 61000-4-6 (immunity to conducted interference)
Test result	Criterion A, 10 Vrms
Test standard	EN 55022 (emitted interference)
Test result	Class A

## Classifications

### eCl@ss

eCl@ss 4.0	24010504
eCl@ss 4.1	24010504
eCl@ss 5.0	19030117
eCl@ss 5.1	19030117
eCl@ss 6.0	19170106
eCl@ss 7.0	19170106
eCl@ss 8.0	19170106

### ETIM

ETIM 3.0	EC000734
ETIM 4.0	EC000734
ETIM 5.0	EC000734

### UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201410
UNSPSC 13.2	43201410

# Industrial Ethernet Switch - FL SWITCH GHS 12G/8-L3 - 2700787

## Approvals

### Approvals

---

#### Approvals

UL Listed / cUL Listed / UL Listed / cUL Listed / cULus Listed

---


#### Ex Approvals

---


#### Approvals submitted

---

### Approval details

UL Listed 

cUL Listed 

UL Listed 

cUL Listed 

cULus Listed 

---