

2702050

https://www.phoenixcontact.com/us/products/2702050

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Security device in PCI format, SD card slot, VPN for 10 VPN tunnels (up to 250 with additional license as an option), intelligent firewall with full scope of functions for maximum security and easy configuration, router with NAT/1:1 NAT, optional CIFS integrity monitoring, can only be used for telepresence applications

## Product description

Software configuration according to Trumpf specification with FW 7.5, can only be used for telepresence applications

#### Commercial data

Item number	2702050
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	DN32
Product key	DNN431
GTIN	4046356920834
Weight per piece (including packing)	163.7 g
Weight per piece (excluding packing)	161.7 g
Customs tariff number	85176200
Country of origin	DE



2702050

https://www.phoenixcontact.com/us/products/2702050

### Technical data

#### Interfaces

Ethernet	
Connection method	RJ45
Transmission speed	10/100 Mbps
Transmission physics	Ethernet in RJ45 twisted pair
Transmission length	100 m (per segment)
Signal LEDs	WAN link, WAN activity, LAN link, LAN activity
No. of channels	2 (RJ45)

### System properties

Fund	

Basic functions	Firewall/Router
System requirements	
Supported browsers	HTTPS support required

# Product type

Format	PCIe x1
Insulation characteristics	
Protection class	III (IEC 61140, EN 61140, VDE 0140-1)

Security routers without DIN rail mounting

#### Electrical properties

Power consumption	max. 2.88 W	
Local diagnostics	One LED per port Activity LED red	
	One LED per port Link active Green LED	
Supply		
Power supply connection	Via PCI bus	

### Connection data

Connection method	RJ45, shielded

### Environmental and real-life conditions

#### Ambient conditions

Degree of protection	IP00
Ambient temperature (operation)	0 °C 70 °C
Permissible humidity (operation)	20 % 90 % (non-condensing)

#### Mounting

Mounting type	PCIe x1-Slot



2702050

https://www.phoenixcontact.com/us/products/2702050

### EMC data

Electromagnetic compatibility

Conformance with EMC Directive 2014/30/EU



2702050

https://www.phoenixcontact.com/us/products/2702050

# Classifications

#### **UNSPSC**

UNSPSC 21.0 43222609



2702050

https://www.phoenixcontact.com/us/products/2702050

# Environmental product compliance

#### EU RoHS

Fulfills EU RoHS substance requirements	Not applicable
Exemption	7(a), 7(c)-l
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com