

Media module - FL SFP SX2 - 2702397

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Gigabit SFP module for transmission up to 2 km with a wavelength of 1310 nm.

Product Description

SFP module with a data transmission speed of 1000 Mbps, a wavelength of 1310 nm, and a maximum transmission length of 2 km.



Key Commercial Data

Packing unit	1 STK
GTIN	 4 055626 163161
GTIN	4055626163161

Technical data

Dimensions

Width	13.7 mm
Height	8.95 mm

Ambient conditions

Ambient temperature (operation)	-40 °C ... 75 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C (non-condensing)

Interfaces

Interface 2	Ethernet FO
No. of ports	1 (LC multi-mode)
Transmission physics	multi-mode fiberglass
Transmission speed	1 Gbps
Transmission length	2 km (Fiberglass 50/125) 1 km (Fiberglass 62.5/125)
Wavelength	1310 nm
Signal LEDs	depending on the Factoryline device

Media module - FL SFP SX2 - 2702397

Technical data

Function

Basic functions	SFP module as FO port
Status and diagnostic indicators	via a Factoryline device

Supply voltage

Supply voltage	3.3 V (via Factoryline switch)
Max. current consumption	300 mA
Current consumption	300 mA

General

Mounting type	Insert in SFP slot
Type AX	Factoryline devices with SFP slot
Net weight	30.4 g
Housing material	Metal

Approvals


Approvals

Approvals


RINA / DNV GL / LR / BSH

Ex Approvals

Approval details

RINA		http://www.rina.org/en	ELE205816XG
------	---	---	-------------

DNV GL		http://exchange.dnv.com/tari/	TAA00000YV
--------	--	---	------------

LR		http://www.lr.org/en	17/20056
----	---	---	----------

BSH		http://www.bsh.de/de/index.jsp	Nr. 966
-----	--	---	---------

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>