

https://www.phoenixcontact.com/us/products/2817864



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Wiring bridge for modules with connecting pitch 17.5 mm, 1-phase, 5-pos.

Your advantages

- · In combination with other devices in the distribution board, such as residual current devices and miniature circuit breakers
- · Practical wiring of all common applications
- · For combinations of lightning and surge arresters

Commercial data

Item number	2817864
Packing unit	1 pc
Minimum order quantity	10 pc
Sales key	CL18
Product key	CL132Z
Catalog page	Page 101 (C-4-2019)
GTIN	4017918148201
Weight per piece (including packing)	24.23 g
Weight per piece (excluding packing)	23.79 g
Customs tariff number	85369095
Country of origin	DE



https://www.phoenixcontact.com/us/products/2817864



Technical data

Product properties

	Туре	Comb bridge		
	Product type	Bridge		
	Number of positions	5		
Electrical properties				
	Number of phases	1		
	Nominal current I _N	100 A		
Dimensions				
	Height	90.8 mm		

Material specifications

Color	Copper
Housing material	Plastic



https://www.phoenixcontact.com/us/products/2817864



Classifications

UNSPSC 21.0

ECLASS

ECLASS-11.0	27371306			
ECLASS-12.0	27371306			
ECLASS-13.0	27371306			
ETIM				
ETIM 9.0	EC000215			
UNSPSC				

39121600



https://www.phoenixcontact.com/us/products/2817864



Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values



https://www.phoenixcontact.com/us/products/2817864



Accessories

CUTFOX-FBS - Front cutter

1212124

https://www.phoenixcontact.com/us/products/1212124



Cutting tool, for separating individual jumper bars from FBS ... plug-in bridges and EB ... insertion bridges

CUTFOX 25 VDE - Cable-cutting tool

1212127

https://www.phoenixcontact.com/us/products/1212127



Cable cutter, precision blade with macro-notching, for copper and aluminum up to 70 mm 2 , VDE 1000 V AC/ 1500 V DC tested

Phoenix Contact 2023 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com