

2832221

https://www.phoenixcontact.com/us/products/2832221

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Patch cable, CAT5, assembled, 1.5 m

Commercial data

Item number	2832221
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	AB11
Product key	ABNABG
Catalog page	Page 721 (C-2-2019)
GTIN	4046356043960
Weight per piece (including packing)	67 g
Weight per piece (excluding packing)	65.7 g
Customs tariff number	85444210
Country of origin	PL



https://www.phoenixcontact.com/us/products/2832221



Technical data

Product properties

Product type	Data cable preassembled
Sensor type	Ethernet
Number of positions	8
Connection profile	RJ45

Electrical properties

Contact resistance	≤ 0.003 Ω (IEC 60603-7)
Nominal voltage U _N	150 V _{rms}
Nominal current I _N	1.5 A
Transmission speed	1 Gbps

Mechanical properties

Mechanical data

Insertion force per signal contact	30.00 N
Extraction force per signal contact	50 N

Material specifications

Flammability rating according to UL 94	V0
Outer sheath, material	LSFROH

Dimensions

Width	12.6 mm
Height	6.6 mm
Length	40.05 mm

External dimensions

External diameter max.	6.2 mm

Connector

Connection 1

Туре	Plug straight RJ45
Shielded	yes
Insertion/withdrawal cycles	≥ 750
Degree of protection	IP20
Number of positions	8
Insertion/withdrawal cycles	750

Connection 2

Connection 2	
Туре	Plug straight RJ45

Cable/line



2832221

https://www.phoenixcontact.com/us/products/2832221

Cable length External cable diameter 5.50 mm Outer sheath, material LSFROH Single wire, number of litz wires 8 Single wire, material Cu litz wire Single wire, cross section 0.14 mm² Shielding SF/UTP Smallest bending radius, fixed installation Halogen-free according to IEC 60754-1 Concentration of fumes Flame resistance 1.50 m 5.50 mm 8 Cu litz wire Cu litz wire 0.14 mm² SF/UTP Smallest bending radius, fixed installation 30 mm Halogen-free according to IEC 60754-1 in accordance with IEC 61034 Flame resistance		
Outer sheath, material Single wire, number of litz wires 8 Single wire, material Cu litz wire Single wire, cross section 0.14 mm² Shielding SF/UTP Smallest bending radius, fixed installation Halogen-free according to IEC 60754-1 Concentration of fumes LSFROH 8 Cu litz wire 0.14 mm² 0.14 mm² SF/UTP Smallest bending radius, fixed installation in accordance with IEC 61034	Cable length	1.50 m
Single wire, number of litz wires Single wire, material Cu litz wire O.14 mm² Shielding SF/UTP Smallest bending radius, fixed installation Halogen-free according to IEC 60754-1 Concentration of fumes 8 Cu litz wire 0.14 mm² SF/UTP Smallest bending radius, fixed installation in accordance with IEC 61034	External cable diameter	5.50 mm
Single wire, material Single wire, cross section O.14 mm² Shielding SF/UTP Smallest bending radius, fixed installation Halogen-free according to IEC 60754-1 Concentration of fumes in accordance with IEC 61034	Outer sheath, material	LSFROH
Single wire, cross section O.14 mm² Shielding Smallest bending radius, fixed installation Halogen-free according to IEC 60754-1 Concentration of fumes in accordance with IEC 61034	Single wire, number of litz wires	8
Shielding SF/UTP Smallest bending radius, fixed installation 30 mm Halogen-free according to IEC 60754-1 Concentration of fumes in accordance with IEC 61034	Single wire, material	Cu litz wire
Smallest bending radius, fixed installation 30 mm Halogen-free according to IEC 60754-1 Concentration of fumes in accordance with IEC 61034	Single wire, cross section	0.14 mm²
Halogen-free according to IEC 60754-1 Concentration of fumes in accordance with IEC 61034	Shielding	SF/UTP
Concentration of fumes in accordance with IEC 61034	Smallest bending radius, fixed installation	30 mm
	Halogen-free	according to IEC 60754-1
Flame resistance according to IEC 60332-3C	Concentration of fumes	in accordance with IEC 61034
	Flame resistance	according to IEC 60332-3C

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-10 °C 60 °C

Standards and regulations

Flame resistance	according to IEC 60332-3C
Concentration of fumes	in accordance with IEC 61034



2832221

https://www.phoenixcontact.com/us/products/2832221

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/2832221



EAC

Approval ID: 19060508



2832221

https://www.phoenixcontact.com/us/products/2832221

Classifications

UNSPSC 21.0

ECLASS

	ECLASS-11.0	27060308	
ı	ECLASS-12.0	27060308	
ı	ECLASS-13.0	27060307	
ETIM			
ı	ETIM 9.0	EC002599	
UNSPSC			

26121600



https://www.phoenixcontact.com/us/products/2832221



Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values



https://www.phoenixcontact.com/us/products/2832221



Accessories

NBC-R4OC/0,3-BC5/R4OC - Patch cable

1227558

https://www.phoenixcontact.com/us/products/1227558



Patch cable, degree of protection: IP20, cable length: 0.3 m, number of positions: 8, CAT5, connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

NBC-R4OC/0,5-BC5/R4OC - Patch cable

1227559

https://www.phoenixcontact.com/us/products/1227559



Patch cable, degree of protection: IP20, cable length: 0.5 m, number of positions: 8, CAT5, connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet



https://www.phoenixcontact.com/us/products/2832221



NBC-R4OC/1,0-BC5/R4OC - Patch cable

1227560

https://www.phoenixcontact.com/us/products/1227560



Patch cable, degree of protection: IP20, cable length: 1 m, number of positions: 8, CAT5, connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

NBC-R4OC/1,5-BC5/R4OC - Patch cable

1227561

https://www.phoenixcontact.com/us/products/1227561



Patch cable, degree of protection: IP20, cable length: 1.5 m, number of positions: 8, CAT5, connection method: Pierce connection, connection cross section: AWG 26-26, cable outlet: straight, Ethernet



https://www.phoenixcontact.com/us/products/2832221



NBC-R4OC/2,0-BC5/R4OC - Patch cable

1227562

https://www.phoenixcontact.com/us/products/1227562



Patch cable, degree of protection: IP20, cable length: 2 m, number of positions: 8, CAT5, connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

NBC-R4OC/3,0-BC5/R4OC - Patch cable

1227563

https://www.phoenixcontact.com/us/products/1227563



Patch cable, degree of protection: IP20, cable length: 3 m, number of positions: 8, CAT5, connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet



https://www.phoenixcontact.com/us/products/2832221



NBC-R4OC/5,0-BC5/R4OC - Patch cable

1227564

https://www.phoenixcontact.com/us/products/1227564



Patch cable, degree of protection: IP20, cable length: 5 m, number of positions: 8, CAT5, connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

NBC-R4OC/7,5-BC5/R4OC - Patch cable

1227565

https://www.phoenixcontact.com/us/products/1227565



Patch cable, degree of protection: IP20, cable length: 7.5 m, number of positions: 8, CAT5, connection method: Pierce connection, connection cross section: AWG 26-26, cable outlet: straight, Ethernet



https://www.phoenixcontact.com/us/products/2832221



NBC-R4OC/0,3-BC6A/R4OC - Patch cable

1227572

https://www.phoenixcontact.com/us/products/1227572



Patch cable, degree of protection: IP20, cable length: 0.3 m, number of positions: 8, 10 Gbps, CAT6_A, connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

NBC-R4OC/0,5-BC6A/R4OC - Patch cable

1227573

https://www.phoenixcontact.com/us/products/1227573



Patch cable, degree of protection: IP20, cable length: 0.5 m, number of positions: 8, 10 Gbps, CAT6_A, connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet



https://www.phoenixcontact.com/us/products/2832221



NBC-R4OC/1,0-BC6A/R4OC - Patch cable

1227575

https://www.phoenixcontact.com/us/products/1227575



Patch cable, degree of protection: IP20, cable length: 1 m, number of positions: 8, 10 Gbps, CAT6_A, connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

NBC-R4OC/1,5-BC6A/R4OC - Patch cable

1227578

https://www.phoenixcontact.com/us/products/1227578



Patch cable, degree of protection: IP20, cable length: 1.5 m, number of positions: 8, 10 Gbps, $CAT6_A$, connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet



https://www.phoenixcontact.com/us/products/2832221



NBC-R4OC/2,0-BC6A/R4OC - Patch cable

1227580

https://www.phoenixcontact.com/us/products/1227580



Patch cable, degree of protection: IP20, cable length: 2 m, number of positions: 8, 10 Gbps, CAT6_A, connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

NBC-R4OC/3,0-BC6A/R4OC - Patch cable

1227581

https://www.phoenixcontact.com/us/products/1227581



Patch cable, degree of protection: IP20, cable length: 3 m, number of positions: 8, 10 Gbps, $CAT6_A$, connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet



https://www.phoenixcontact.com/us/products/2832221



NBC-R4OC/5,0-BC6A/R4OC - Patch cable

1227583

https://www.phoenixcontact.com/us/products/1227583



Patch cable, degree of protection: IP20, cable length: 5 m, number of positions: 8, 10 Gbps, $CAT6_A$, connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

NBC-R4OC/7,5-BC6A/R4OC - Patch cable

1227585

https://www.phoenixcontact.com/us/products/1227585



Patch cable, degree of protection: IP20, cable length: 7.5 m, number of positions: 8, 10 Gbps, $CAT6_A$, connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet



https://www.phoenixcontact.com/us/products/2832221



NBC-R4OC/10,0-BC6A/R4OC - Patch cable

1227588

https://www.phoenixcontact.com/us/products/1227588



Patch cable, degree of protection: IP20, cable length: 10 m, number of positions: 8, 10 Gbps, CAT6_A, connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

NBC-R4OC/12,5-BC6A/R4OC - Patch cable

1227590

https://www.phoenixcontact.com/us/products/1227590



Patch cable, degree of protection: IP20, cable length: 12.5 m, number of positions: 8, 10 Gbps, CAT6_A, connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet



https://www.phoenixcontact.com/us/products/2832221



NBC-R4OC/15,0-BC6A/R4OC - Patch cable

1227591

https://www.phoenixcontact.com/us/products/1227591



Patch cable, degree of protection: IP20, cable length: 15 m, number of positions: 8, 10 Gbps, $CAT6_A$, connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

NBC-R4OC/20,0-BC6A/R4OC - Patch cable

1227593

https://www.phoenixcontact.com/us/products/1227593



Patch cable, degree of protection: IP20, cable length: 20 m, number of positions: 8, 10 Gbps, $CAT6_A$, connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

Phoenix Contact 2023 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com