#### 2832580

https://www.phoenixcontact.com/us/products/2832580

**PHŒNIX** CONTACT

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Patch cable, CAT5, assembled, 5 m

### Commercial data

Item number	2832580
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	AB11
Product key	ABNABG
Catalog page	Page 721 (C-2-2019)
GTIN	4046356044080
Weight per piece (including packing)	181 g
Weight per piece (excluding packing)	22.22 g
Customs tariff number	85444210
Country of origin	PL



https://www.phoenixcontact.com/us/products/2832580



### Technical data

### Product properties

Product type	Data cable preassembled
Sensor type	Ethernet
Number of positions	8
Connection profile	RJ45

#### **Electrical properties**

Contact resistance	≤ 0.003 Ω (IEC 60603-7)
Nominal voltage U <sub>N</sub>	150 V <sub>rms</sub>
Nominal current I <sub>N</sub>	1.5 A
Transmission speed	1 Gbps

### Mechanical properties

Mechanical data		
Insertion force per signal contact	30.00 N	
Extraction force per signal contact	50 N	

#### Material specifications

Flammability rating according to UL 94	V0
Outer sheath, material	LSFROH

#### Dimensions

Width	12.6 mm	
Height	6.6 mm	
Length	40.05 mm	
External dimensions		
External diameter max.	6.2 mm	

### Connector

#### Connection 1

Туре	Plug straight RJ45	
Shielded	yes	
Insertion/withdrawal cycles	≥ 750	
Degree of protection	IP20	
Number of positions	8	
Insertion/withdrawal cycles	750	
Connection 2		
Туре	Plug straight RJ45	



https://www.phoenixcontact.com/us/products/2832580

Cable length	5.00 m
External cable diameter	5.50 mm
Outer sheath, material	LSFROH
Single wire, number of litz wires	8
Single wire, material	Cu litz wire
Single wire, cross section	0.14 mm <sup>2</sup>
Shielding	SF/UTP
Smallest bending radius, fixed installation	30 mm
Halogen-free	according to IEC 60754-1
Concentration of fumes	in accordance with IEC 61034
Flame resistance	according to IEC 60332-3C

#### Environmental and real-life conditions

Ambient conditions		
Degree of protection	IP20	
Ambient temperature (operation)	-10 °C 60 °C	

#### Standards and regulations

Flame resistance	according to IEC 60332-3C
Concentration of fumes	in accordance with IEC 61034

**PHŒNIX** CONTACT

2832580

https://www.phoenixcontact.com/us/products/2832580



### Approvals

🌣 To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/2832580

EAC Approval ID: 19060508

2832580

https://www.phoenixcontact.com/us/products/2832580




### Classifications

### ECLASS

ECLASS-12.0 27060308 ECLASS-13.0 27060307	ECLASS-11.0	27060308
ECLASS-13.0 27060307	ECLASS-12.0	27060308
	ECLASS-13.0	27060307

### ETIM

	ETIM 9.0	EC002599
UN	ISPSC	
	UNSPSC 21.0	26121600



2832580 https://www.phoenixcontact.com/us/products/2832580



### Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

2832580

https://www.phoenixcontact.com/us/products/2832580



Accessories

NBC-R4OC/0,3-BC5/R4OC - Patch cable

1227558 https://www.phoenixcontact.com/us/products/1227558



Patch cable, degree of protection: IP20, cable length: 0.3 m, number of positions: 8, CAT5, connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

### NBC-R4OC/0,5-BC5/R4OC - Patch cable

1227559

https://www.phoenixcontact.com/us/products/1227559



Patch cable, degree of protection: IP20, cable length: 0.5 m, number of positions: 8, CAT5, connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

2832580

https://www.phoenixcontact.com/us/products/2832580



NBC-R4OC/1,0-BC5/R4OC - Patch cable

#### 1227560

https://www.phoenixcontact.com/us/products/1227560



Patch cable, degree of protection: IP20, cable length: 1 m, number of positions: 8, CAT5, connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

### NBC-R4OC/1,5-BC5/R4OC - Patch cable

1227561 https://www.phoenixcontact.com/us/products/1227561



Patch cable, degree of protection: IP20, cable length: 1.5 m, number of positions: 8, CAT5, connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

2832580

https://www.phoenixcontact.com/us/products/2832580



NBC-R4OC/2,0-BC5/R4OC - Patch cable

1227562

https://www.phoenixcontact.com/us/products/1227562



Patch cable, degree of protection: IP20, cable length: 2 m, number of positions: 8, CAT5, connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

### NBC-R4OC/3,0-BC5/R4OC - Patch cable

1227563 https://www.phoenixcontact.com/us/products/1227563



Patch cable, degree of protection: IP20, cable length: 3 m, number of positions: 8, CAT5, connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

2832580

https://www.phoenixcontact.com/us/products/2832580



NBC-R4OC/5,0-BC5/R4OC - Patch cable

#### 1227564

https://www.phoenixcontact.com/us/products/1227564



Patch cable, degree of protection: IP20, cable length: 5 m, number of positions: 8, CAT5, connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

### NBC-R4OC/7,5-BC5/R4OC - Patch cable

1227565 https://www.phoenixcontact.com/us/products/1227565



Patch cable, degree of protection: IP20, cable length: 7.5 m, number of positions: 8, CAT5, connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

2832580

https://www.phoenixcontact.com/us/products/2832580



NBC-R4OC/0,3-BC6A/R4OC - Patch cable

1227572

https://www.phoenixcontact.com/us/products/1227572



Patch cable, degree of protection: IP20, cable length: 0.3 m, number of positions: 8, 10 Gbps,  $CAT6_A$ , connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

#### NBC-R4OC/0,5-BC6A/R4OC - Patch cable

1227573 https://www.phoenixcontact.com/us/products/1227573



Patch cable, degree of protection: IP20, cable length: 0.5 m, number of positions: 8, 10 Gbps,  $CAT6_A$ , connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

2832580

https://www.phoenixcontact.com/us/products/2832580



NBC-R4OC/1,0-BC6A/R4OC - Patch cable

1227575

https://www.phoenixcontact.com/us/products/1227575



Patch cable, degree of protection: IP20, cable length: 1 m, number of positions: 8, 10 Gbps,  $CAT6_A$ , connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

#### NBC-R4OC/1,5-BC6A/R4OC - Patch cable

1227578 https://www.phoenixcontact.com/us/products/1227578



Patch cable, degree of protection: IP20, cable length: 1.5 m, number of positions: 8, 10 Gbps,  $CAT6_A$ , connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

2832580

https://www.phoenixcontact.com/us/products/2832580



NBC-R4OC/2,0-BC6A/R4OC - Patch cable

#### 1227580

https://www.phoenixcontact.com/us/products/1227580



Patch cable, degree of protection: IP20, cable length: 2 m, number of positions: 8, 10 Gbps,  $CAT6_A$ , connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

#### NBC-R4OC/3,0-BC6A/R4OC - Patch cable

1227581 https://www.phoenixcontact.com/us/products/1227581



Patch cable, degree of protection: IP20, cable length: 3 m, number of positions: 8, 10 Gbps,  $CAT6_A$ , connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

2832580

https://www.phoenixcontact.com/us/products/2832580



NBC-R4OC/5,0-BC6A/R4OC - Patch cable

#### 1227583

https://www.phoenixcontact.com/us/products/1227583



Patch cable, degree of protection: IP20, cable length: 5 m, number of positions: 8, 10 Gbps,  $CAT6_A$ , connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

#### NBC-R4OC/7,5-BC6A/R4OC - Patch cable

1227585 https://www.phoenixcontact.com/us/products/1227585



Patch cable, degree of protection: IP20, cable length: 7.5 m, number of positions: 8, 10 Gbps,  $CAT6_A$ , connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

2832580

https://www.phoenixcontact.com/us/products/2832580



NBC-R4OC/10,0-BC6A/R4OC - Patch cable

#### 1227588

https://www.phoenixcontact.com/us/products/1227588



Patch cable, degree of protection: IP20, cable length: 10 m, number of positions: 8, 10 Gbps,  $CAT6_A$ , connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

#### NBC-R4OC/12,5-BC6A/R4OC - Patch cable

1227590 https://www.phoenixcontact.com/us/products/1227590



Patch cable, degree of protection: IP20, cable length: 12.5 m, number of positions: 8, 10 Gbps,  $CAT6_A$ , connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

2832580

https://www.phoenixcontact.com/us/products/2832580



#### NBC-R4OC/15,0-BC6A/R4OC - Patch cable

1227591

https://www.phoenixcontact.com/us/products/1227591



Patch cable, degree of protection: IP20, cable length: 15 m, number of positions: 8, 10 Gbps, CAT6<sub>A</sub>, connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

#### NBC-R4OC/20,0-BC6A/R4OC - Patch cable

1227593 https://www.phoenixcontact.com/us/products/1227593



Patch cable, degree of protection: IP20, cable length: 20 m, number of positions: 8, 10 Gbps,  $CAT6_A$ , connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

Phoenix Contact 2023 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com