

EMD-FL-PF-400 - Monitoring relay



2885809

<https://www.phoenixcontact.com/us/products/2885809>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Monitoring relay for load monitoring ($\cos \phi = 0,1 \dots 1$) in 1- and 3-phase networks, underload, overload, window, error memory, wide range power supply unit, 2 changeover contacts

Product description

Increasingly higher demands are being placed on safety and system availability - across all sectors. Processes are becoming more and more complex, not only in mechanical engineering and the chemical industry, but also in plant and automation technology. Demands on power engineering are also increasing constantly.

Error-free and therefore cost-effective operation can only be achieved through continuous monitoring of important network and system parameters. Electronic monitoring relays in the EMD series are available for a wide range of monitoring tasks to avoid the consequences of errors or to keep them within limits.

The operating states are indicated using colored LEDs, errors that may occur can be sent to a control system via a floating contact or can shut down a part of the system. Some device versions are equipped with startup and response delays in order to briefly tolerate measured values outside the set monitoring range.

Your advantages

- Monitoring range up to 7.2 kW
- Temperature monitoring of the motor winding
- Separately adjustable startup and response delays
- Variable supply voltage range
- Detection of switched off loads

Commercial data

Item number	2885809
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	C440
Product key	CK4131
Catalog page	Page 254 (C-5-2019)
GTIN	4046356100779
Weight per piece (including packing)	167.6 g
Weight per piece (excluding packing)	167.6 g
Customs tariff number	85364900
Country of origin	AT

EMD-FL-PF-400 - Monitoring relay



2885809

<https://www.phoenixcontact.com/us/products/2885809>

Technical data

Notes

Utilization restriction

EMC note	EMC: class A product, see manufacturer's declaration in the download area
----------	---

Product properties

Product type	Load monitoring relay
Operating mode	100% operating factor
Mechanical service life	approx. 2×10^7 cycles

Insulation characteristics

Insulation	Basic insulation
------------	------------------

Insulation characteristics

Insulation	Basic insulation
Overvoltage category	III
Pollution degree	2

Electrical properties

Service life electrical	2×10^5 cycles at ohmic load, 1000 VA
Mains type	1 and 3-phase
Rated insulation voltage	300 V
Rated surge voltage	4 kV

Supply

Supply voltage range	24 V AC ... 240 V AC -15 % ... +10 % 24 V DC ... 240 V DC (-20 % ... +25 %)
Type of supply voltage	AC/DC
Nominal power consumption	4.5 VA (1.5 W)

Input data

Input name	Measuring input
Measured value	AC sine (10 ... 100 Hz)
Nominal input voltage U_N	3 N ~ 415/240 V
Input voltage range	40 V AC ... 415 V AC (1(N) ~, single-phase load) 40 V AC ... 415 V AC (3(N) ~, 3-phase load)
Maximum input voltage	3 N ~ 500/289 V
Input current range	0.5 A ... 10 A (Connection terminal blocks: L1i and L1k)
Overload capacity	12 A permanent
Input resistance of voltage input	$\geq 1 \text{ M}\Omega$
Input resistance current input	5 m Ω
Min. switching threshold $\cos \varphi$	0.1 ... 0.99
Max. switching threshold $\cos \varphi$	0.2 ... 1

EMD-FL-PF-400 - Monitoring relay



2885809

<https://www.phoenixcontact.com/us/products/2885809>

Frequency range	48 Hz ... 400 Hz
Maximum temperature coefficient	≤ 0.1 %/K
Setting range for response delay	0.1 s ... 40 s
Setting range for starting delay	1 s ... 100 s
Function	Underload Overload Window Error memory
Basic accuracy	± 5 % (At cos φ = 0.8)
Setting accuracy	≤ 5 % (At cos φ = 0.8)
Repeat accuracy	± 1.8 %
Recovery time	500 ms

Output data

Switching

Contact switching type	2 floating changeover contacts
Maximum switching voltage	250 V AC (in acc. with IEC 60664-1)
Interrupting rating (ohmic load) max.	750 VA (3 A/250 V AC, module aligned, ≤ 5 mm spacing) 1250 VA (5 A/250 V AC, module not aligned, ≥ 5 mm spacing)
Output fuse	5 A (fast-blow)

Connection data

Connection method	Screw connection
Stripping length	8 mm
Conductor cross section rigid	0.5 mm ² ... 2.5 mm ²
Conductor cross section flexible	0.25 mm ² ... 2.5 mm ²
Conductor cross section AWG	20 ... 14

Dimensions

Width	22.5 mm
Height	90 mm
Depth	113 mm

Material specifications

Housing insulation material	Polyamide PA, self-extinguishing
-----------------------------	----------------------------------

Environmental and real-life conditions

Ambient conditions

Degree of protection (Housing)	IP40 (Housing)
Degree of protection (Connection terminal blocks)	IP20 (Connection terminal blocks)
Ambient temperature (operation)	-25 °C ... 55 °C -25 °C ... 40 °C (corresponds to UL 508)
Ambient temperature (storage/transport)	-25 °C ... 70 °C
Climatic class	3K3 (in acc. with EN 60721)

EMD-FL-PF-400 - Monitoring relay



2885809

<https://www.phoenixcontact.com/us/products/2885809>

Permissible humidity (operation)	15 % ... 85 %
----------------------------------	---------------

Approvals

CE

Certificate	CE-compliant
-------------	--------------

UL, USA/Canada

Identification	UL/C-UL Listed UL 508
----------------	-----------------------

EMC data

Low Voltage Directive	Conformance with Low Voltage Directive
Noise immunity	EN 61000-6-2
Electromagnetic compatibility	Conformance with EMC directive
Noise emission	EN 61000-6-4

Standards and regulations

Standards/regulations	EN 50178
-----------------------	----------

Mounting

Mounting type	DIN rail mounting
Assembly instructions	on standard DIN rail NS 35 in accordance with EN 60715
Mounting position	any


EMD-FL-PF-400 - Monitoring relay

2885809

<https://www.phoenixcontact.com/us/products/2885809>

Drawings

Block diagram



EMD-FL-PF-400 - Monitoring relay



2885809

<https://www.phoenixcontact.com/us/products/2885809>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2885809>



EAC

Approval ID: TR_TS_D_00573_c



EAC

Approval ID: RU*C-DE.*08.B.00010



UL Listed

Approval ID: FILE E 172140



cUL Listed

Approval ID: FILE E 172140

cULus Listed

EMD-FL-PF-400 - Monitoring relay



2885809

<https://www.phoenixcontact.com/us/products/2885809>

Classifications

ECLASS

ECLASS-11.0	27371016
ECLASS-13.0	27371016
ECLASS-12.0	27371016

ETIM

ETIM 9.0	EC002055
----------	----------

UNSPSC

UNSPSC 21.0	39121100
-------------	----------

EMD-FL-PF-400 - Monitoring relay



2885809

<https://www.phoenixcontact.com/us/products/2885809>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e No hazardous substances above threshold values
------------	---

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com