

Power module - FL SWITCH 4800E-P1 - 2891075

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Modular power supply for FL SWITCH 48... managed switches. Wide input voltage range 36 V DC to 75 V DC.



Why buy this product

- Network structure according to IEC 61850
- IEEE 1613



IEC 61850-3

Key Commercial Data

Packing unit	1 STK
Weight per Piece (excluding packing)	1,150.000 g
Custom tariff number	85176200
Country of origin	Taiwan

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Dimensions

Width	151 mm
Height	40 mm
Depth	214 mm

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 75 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Permissible humidity (operation)	5 % ... 95 % (non-condensing)

Power module - FL SWITCH 4800E-P1 - 2891075

Technical data

Input data

Nominal input voltage	48 V DC
Nominal input voltage range	36 V DC ... 75 V DC

General

Net weight	836 g
Degree of protection	IP20

Connection data, input

Connection method	Screw connection
Conductor cross section solid min.	0.8 mm ²
Conductor cross section solid max.	6 mm ²
Conductor cross section flexible min.	0.8 mm ²
Conductor cross section flexible max.	6 mm ²
Conductor cross section AWG min.	18
Conductor cross section AWG max.	10