

Article

2902992

 from revision

00

 Designation

UNO-PS/1AC/24DC/60W

Device category 3 - electrical article

Prediction done by: psba02

				based on	Environmental condition	MTTF in h	MTTF in a	failure rate in FIT (λ basis)			
at	<table border="1" style="display: inline-table; border-collapse: collapse;"><tr><td style="width: 30px;">40</td></tr></table>	40	°C with	<table border="1" style="display: inline-table; border-collapse: collapse;"><tr><td style="width: 50px;">100,00</td></tr></table>	100,00	% duty cycle	SN 29500	GB, GC - Ground Benign, Controlled	785787	89,7	1272,609
40											
100,00											
at	<table border="1" style="display: inline-table; border-collapse: collapse;"><tr><td style="width: 30px;"></td></tr></table>		°C with	<table border="1" style="display: inline-table; border-collapse: collapse;"><tr><td style="width: 50px;"></td></tr></table>		% duty cycle			-	-	
at	<table border="1" style="display: inline-table; border-collapse: collapse;"><tr><td style="width: 30px;"></td></tr></table>		°C with	<table border="1" style="display: inline-table; border-collapse: collapse;"><tr><td style="width: 50px;"></td></tr></table>		% duty cycle			-	-	
at	<table border="1" style="display: inline-table; border-collapse: collapse;"><tr><td style="width: 30px;"></td></tr></table>		°C with	<table border="1" style="display: inline-table; border-collapse: collapse;"><tr><td style="width: 50px;"></td></tr></table>		% duty cycle			-	-	
at	<table border="1" style="display: inline-table; border-collapse: collapse;"><tr><td style="width: 30px;"></td></tr></table>		°C with	<table border="1" style="display: inline-table; border-collapse: collapse;"><tr><td style="width: 50px;"></td></tr></table>		% duty cycle			-	-	
at	<table border="1" style="display: inline-table; border-collapse: collapse;"><tr><td style="width: 30px;"></td></tr></table>		°C with	<table border="1" style="display: inline-table; border-collapse: collapse;"><tr><td style="width: 50px;"></td></tr></table>		% duty cycle			-	-	