

Article from revision
 Designation

Device category 3 - electrical article

Prediction done by: psba02

| | | | | based on | Environmental condition | MTTF in h | MTTF in a | failure rate in FIT (λ basis) |
|----|---------------------------------|---------|-------------------------------------|---------------------------------------|---|--------------------------------------|-------------------------------------|--|
| at | <input type="text" value="40"/> | °C with | <input type="text" value="100,00"/> | <input type="text" value="SN 29500"/> | <input type="text" value="GB, GC - Ground Benign, Controlled"/> | <input type="text" value="1201496"/> | <input type="text" value="137,16"/> | <input type="text" value="832,296"/> |
| at | <input type="text"/> | °C with | <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text" value="-"/> | <input type="text" value="-"/> | <input type="text"/> |
| at | <input type="text"/> | °C with | <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text" value="-"/> | <input type="text" value="-"/> | <input type="text"/> |
| at | <input type="text"/> | °C with | <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text" value="-"/> | <input type="text" value="-"/> | <input type="text"/> |
| at | <input type="text"/> | °C with | <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text" value="-"/> | <input type="text" value="-"/> | <input type="text"/> |
| at | <input type="text"/> | °C with | <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text" value="-"/> | <input type="text" value="-"/> | <input type="text"/> |