

# Timer relay - PLC-TR-1T-MUL-300M




2910140

<https://www.phoenixcontact.com/us/products/2910140>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

---



Multi-function timer relay with 4 functions in an ultra-narrow design, adjustable time range (0.1 s - 300 min), 1 changeover contact, screw connection

---

# Timer relay - PLC-TR-1T-MUL-300M



2910140

<https://www.phoenixcontact.com/us/products/2910140>

## Commercial Data

Item number	2910140
Packing unit	1 pc
Minimum order quantity	1 pc
Sales Key	C04
Product Key	CK4521
Catalog Page	Page 262 (C-5-2019)
GTIN	4055626430492
Weight per Piece (including packing)	59.6 g
Weight per Piece (excluding packing)	50.9 g
Customs tariff number	85364900
Country of origin	DE

# Timer relay - PLC-TR-1T-MUL-300M



2910140

<https://www.phoenixcontact.com/us/products/2910140>

## Technical Data

### Product properties

Product type	Timer relay
Operating mode	100% operating factor
Mechanical service life	approx. $2 \times 10^7$ cycles

### Insulation characteristics

Overvoltage category	III
Pollution degree	2
Insulation	Basic insulation

### Electrical properties

Service life electrical	approx. $2 \times 10^5$ cycles at ohmic load, 1000 VA
Nominal power consumption	0.45 W (at 24 V DC)
Rated insulation voltage	300 V AC
Rated surge voltage	6 kV

### Input data

Nominal power consumption	0.45 W (at 24 V DC)
Input voltage range	24 V DC (19.2 V DC ... 30 V DC)
Recovery time	50 ms
Setting range time	0.1 s ... 300 min. (4 time end ranges)
Setting accuracy	$\leq 2.5$ % (of scale end value)
Repeat accuracy	$\leq 0.5$ % (of scale end value)

### Control

Connection name	Non-floating, terminals A1-B1
Control pulse length	$\geq 50$ ms

### Output data

#### Switching

Contact type	1 floating changeover contact
Maximum switching voltage	250 V AC
Interrupting rating (ohmic load) max.	1500 VA (6 A / 250 V AC)
Output fuse	6.3 A (fast-blow)

### Connection data

Connection method	Screw connection
Stripping length	8 mm
Conductor cross section solid	0.14 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
Conductor cross section flexible	0.14 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
Conductor cross section AWG	30 ... 12
Torque	0.6 Nm ... 0.8 Nm ( )

# Timer relay - PLC-TR-1T-MUL-300M



2910140

<https://www.phoenixcontact.com/us/products/2910140>

5 lb<sub>F</sub>-in. ... 7 lb<sub>F</sub>-in.

## LED signaling

Status display	Green LED (POWER)
	Yellow LED (relay active)

## Dimensions

Width	6.2 mm
Height	80 mm
Depth	86 mm

## Material specifications

Flammability rating according to UL 94	V0
Housing insulation material	Polyamide PA, self-extinguishing

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-20 °C ... 65 °C
Ambient temperature (storage/transport)	-25 °C ... 80 °C
Altitude	≤ 2000 m
Permissible humidity (operation)	15 % ... 85 %

## Approval data

### CE

Identification	CE-compliant
----------------	--------------

### CE

Identification	UL/C-UL Listed UL 508
----------------	-----------------------

## EMC data

Low Voltage Directive	Conformance with Low Voltage Directive
Electromagnetic compatibility	Conformance with EMC directive
Noise emission	EN 61000-6-3
Noise immunity	EN 61000-6-2

## Standards and regulations

Standards/regulations	IEC 61812-1
	IEC 60947-5-1

## Mounting

Mounting type	DIN rail mounting
Assembly instructions	on standard DIN rail NS 35 in accordance with EN 60715
Mounting position	any

# Timer relay - PLC-TR-1T-MUL-300M



2910140

<https://www.phoenixcontact.com/us/products/2910140>

## Approvals



### DNV GL

Approval ID: TAA00002RX

Nominal Voltage  $U_N$

Nominal Current  $I_N$

Cross Section AWG

Cross Section  $\text{mm}^2$

-

-



### UL Listed

Approval ID: FILE E 172140



### cUL Listed

Approval ID: FILE E 172140

cULus Listed

# Timer relay - PLC-TR-1T-MUL-300M



2910140

<https://www.phoenixcontact.com/us/products/2910140>

## Classifications

### ECLASS

ECLASS-9.0	27371605
ECLASS-10.0.1	27371605
ECLASS-11.0	27371605

### ETIM

ETIM 8.0	EC001439
----------	----------

### UNSPSC

UNSPSC 21.0	39122300
-------------	----------

# Timer relay - PLC-TR-1T-MUL-300M



2910140

<https://www.phoenixcontact.com/us/products/2910140>

## Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2022 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)