

# MINI-PS-100-240AC/2X15DC/1


Order No.: 2938743



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2938743>

DIN rail power supply unit 2x15 V DC/1 A, primary-switched mode, slim design



Commercial data	
GTIN (EAN)	 4 017918 906870
Note	Made-to-order
sales group	H042
Pack	1 pcs.
Customs tariff	85044082
Catalog page information	Page 599 (IF-2011)

### Product notes

WEEE/RoHS-compliant since:  
03/01/2006



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

### Product description

MINI POWER is the extremely slim power supply unit with constructional widths of 22.5 mm, 45 mm and 67.5 mm.

In addition to a 24 V DC version with output currents of 1 A , 2 A and 4 A ,special voltages with 5 V/3 A,  $\pm 15$  V/1 A and 10 V ... 15 V/2A are also available.

Reliable startup of heavy loads is ensured by a power reserve of up to 100 % – the POWER BOOST.

The high operational reliability is thus dependably guaranteed in complex global networks as well. MINI POWER also functions in applications where static voltage dips, transient failures of the supply voltage or phase failure are to be expected.

Generously dimensioned capacitors guarantee a mains buffering time of more than 20 ms under full load.

#### Technical data

##### Input data

Nominal input voltage	100 V AC ... 240 V AC
AC input voltage range	85 V AC ... 264 V AC
DC input voltage range	90 V DC ... 350 V DC
AC frequency range	45 Hz ... 65 Hz
DC frequency range	0 Hz
Current consumption	Approx. 0.6 A (120 V AC) Approx. 0.4 A (230 V AC) Approx. 0.8 A (90 V DC) Approx. 0.3 A (350 V DC)
Nominal power consumption	15 W
Inrush surge current	< 35 A (typical)
Power failure bypass	> 30 ms (120 V AC) > 150 ms (230 V AC)
Input fuse	2.5 A (slow-blow, internal)
Permissible backup fuse	6 A 10 A 16 A
Additional text	characteristic B

##### Output data

Nominal output voltage	$\pm 15$ V DC $\pm 1\%$
Output current	2x 1 A (-25 °C ... 60 °C) 2x 1.5 A (with POWER BOOST, -25°C ... 40°C permanent)
Derating	60 °C ... 70 °C (2.5%/K)
Connection in parallel	Yes, for assembling redundant systems and increasing efficiency
Connection in series	Yes
Current limitation	Approx 4.4 A (in the event of a short circuit)
Control deviation	< 2 % (change in load, static 10% ... 90%) < 3 % (change in load, dynamic 10% ... 90%) < 0.1 % (change in input voltage $\pm 10\%$ )

Residual ripple	< 30 mV <sub>pp</sub> (20 MHz)
Peak switching voltages nominal load	< 20 mV <sub>pp</sub> (20 MHz)
Maximum power dissipation idling	2 W
Power loss nominal load max.	8 W
<b>General data</b>	
Width	45 mm
Height	99 mm
Depth	107 mm
Net weight	0.25 kg
Operating voltage display	Green LED
Efficiency	> 80 % (At 230 V AC and nominal values)
Insulation voltage input/output	3 kV (routine test) 4 kV (type test)
Degree of protection	IP20
Protection class	II (in an enclosed control cabinet)
MTBF (IEC 61709, SN 29500)	> 500000 h
Ambient temperature (operation)	-25 °C ... 70 °C (> 60 °C derating)
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Max. permissible relative humidity (operation)	≤ 95 % (at 25 °C, no condensation)
Mounting position	horizontal DIN rail NS 35, EN 60715
Assembly instructions	Can be aligned: Horizontal 0 cm, vertical 5 cm
Electromagnetic compatibility	Conformance with EMC Directive 2004/108/EC
Noise emission	EN 50081-2
Noise immunity	EN 61000-6-2:2005
Low Voltage Directive	Conformance with LV directive 2006/95/EC
Standard - Safety of transformers	EN 61558-2-17
Standard - Electrical safety	EN 60950-1/VDE 0805 (SELV)
Standard – Electronic equipment for use in electrical power installations and their assembly into electrical power installations	EN 50178/VDE 0160 (PELV)
Standard - Safe isolation	DIN VDE 0100-410 DIN VDE 0106-1010
Standard – Limitation of mains harmonic currents	EN 61000-3-2
Standard – Equipment safety	GS (tested safety)

UL approvals	UL/C-UL listed UL 508
	UL/C-UL Recognized UL 60950
	UL/C-UL Listed UL 1604 Class I, Division 2, Groups A, B, C, D

#### Connection data, input

Connection method	Pluggable screw connection
Conductor cross section solid min.	0.2 mm <sup>2</sup>
Conductor cross section solid max.	2.5 mm <sup>2</sup>
Conductor cross section stranded min.	0.2 mm <sup>2</sup>
Conductor cross section stranded max.	2.5 mm <sup>2</sup>
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12
Stripping length	7 mm
Screw thread	M3

#### Connection data, output

Connection method	Pluggable screw connection
Conductor cross section solid min.	0.2 mm <sup>2</sup>
Conductor cross section solid max.	2.5 mm <sup>2</sup>
Conductor cross section stranded min.	0.2 mm <sup>2</sup>
Conductor cross section stranded max.	2.5 mm <sup>2</sup>
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12
Stripping length	7 mm

#### Signaling

Output name	DC OK active
Status display	"DC OK" LED green
Conductor cross section solid min.	0.2 mm <sup>2</sup>
Conductor cross section solid max.	2.5 mm <sup>2</sup>
Conductor cross section stranded min.	0.2 mm <sup>2</sup>
Conductor cross section stranded max.	2.5 mm <sup>2</sup>
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12
Screw thread	M3

## Certificates / Approvals



Certification


CUL, CUL Listed, GOST, UL, UL Listed

Certification Ex:

CUL-EX LIS, UL-EX LIS

## Diagrams/Drawings

Block diagram



**Address**

PHOENIX CONTACT Inc., USA  
586 Fulling Mill Road  
Middletown, PA 17057, USA  
Phone (800) 888-7388  
Fax (717) 944-1625  
<http://www.phoenixcon.com>



© 2011 Phoenix Contact  
Technical modifications reserved;