


REL-MR-G 24/1 - Single relay

2961037

<https://www.phoenixcontact.com/us/products/2961037>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Pluggable replacement miniature relay, 1 N/O contact, input voltage 24 V DC



Commercial data

Item number	2961037
Packing unit	1 pc
Minimum order quantity	8 pc
Note	Made to order (non-returnable)
Sales key	C460
Product key	CK6191
Catalog page	Page 524 (C-5-2019)
GTIN	4017918087074
Weight per piece (including packing)	5.987 g
Weight per piece (excluding packing)	4.387 g
Customs tariff number	85364190
Country of origin	DE

Technical data

Product properties

Product type	Single relay
Operating mode	100% operating factor
Mechanical service life	approx. 2×10^7 cycles

Electrical properties

Maximum power dissipation for nominal condition	0.12 W
Test voltage (Winding/contact)	2 kV AC (50 Hz, 1 min., winding/contact)

Input data

Coil side

Nominal input voltage U_N	24 V DC
Input voltage range	19.2 V DC ... 26.4 V DC (20 °C)
Drive and function	monostable
Drive (polarity)	non-polarized
Typical input current at U_N	5 mA
Typical response time	5 ms
Typical release time	2 ms
Coil resistance	4800 Ω \pm 10 %

Output data

Switching

Contact switching type	1 N/O contact
Type of switch contact	Double contact
Contact material	AgNi, hard gold-plated
Maximum switching voltage	250 V AC 125 V DC
Minimum switching voltage	5 V DC
Limiting continuous current	3 A
Maximum inrush current	5 A
Min. switching current	1 mA
Interrupting rating (ohmic load) max.	72 W (at 24 V DC) 60 W (at 48 V DC) 50 W (at 60 V DC) 50 W (at 110 V DC) 750 VA (for 230 V AC)

Dimensions

Width	5 mm
Height	23 mm
Depth	17 mm

REL-MR-G 24/1 - Single relay



2961037

<https://www.phoenixcontact.com/us/products/2961037>

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C

Standards and regulations

Standards/regulations	DIN VDE 0110
	IEC 255/DIN VDE 0435 (in relevant parts)

Mounting

Mounting position	any
-------------------	-----

REL-MR-G 24/1 - Single relay


2961037

<https://www.phoenixcontact.com/us/products/2961037>



Drawings

Schematic diagram




REL-MR-G 24/1 - Single relay

2961037

<https://www.phoenixcontact.com/us/products/2961037>



Circuit diagram



REL-MR-G 24/1 - Single relay



2961037

<https://www.phoenixcontact.com/us/products/2961037>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2961037>



EAC

Approval ID: TR_TS_D_00573_c



EAC

Approval ID: RU*C-DE.*08.B.00010

REL-MR-G 24/1 - Single relay



2961037

<https://www.phoenixcontact.com/us/products/2961037>

Classifications

ECLASS

ECLASS-11.0	27371601
ECLASS-12.0	27371601
ECLASS-13.0	27371601

ETIM

ETIM 8.0	EC001437
----------	----------

UNSPSC

UNSPSC 21.0	39122300
-------------	----------

REL-MR-G 24/1 - Single relay



2961037

<https://www.phoenixcontact.com/us/products/2961037>

Environmental product compliance

China RoHS	Environmentally Friendly Use Period = 50 years For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"
------------	--

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com