

Reliability Prediction Assessment

The given failure rates refer to more than one article. For the valid articles please refer to the article list.

Device category 3 - electronical article

- 7	r	edi	cti	on	done	hv.	pyti0
		cu			aone	Dy.	Pytio

at	25	°C with	21,00	% duty cycle
at	40	°C with	34,25	% duty cycle
at	40	°C with	100,00	% duty cycle
at		°C with		% duty cycle
at		°C with		% duty cycle
at		°C with		% duty cycle

based on
SN 29500

GB, GC - Ground Be	nign, Controlled

MTTF in h	MTT
-	
12658227,85	14
-	
-	

	failure rate in FIT (λ basis)
_	70
_	79
⊢	



Reliability Prediction Assessment

Article list

Autiolo	from revision	Designation
Article	HOIII TEVISION	Designation OPT-60DC/230AC/ 2 OPT- 5DC/230AC/ 2
2982184 2982168	02	OPT-60DC/230AC/ 2
2982168	02	OPT- 5DC/230AC/ 2
2967950 2982171	02	OPT-24DC/230AC/ 1
2082171	02	OPT-24DC/230AC/ 2
2902171	02	OPT 00D0/000A0/ 2
2967963	02	OPT-60DC/230AC/ 1
	,	
—	—	
—		-
	-	
	<u> </u>	
—		-
—		
<u> </u>		
—		-
<u> </u>	<u> </u>	
\vdash		-
\vdash		
\vdash		
\vdash		-

PHOENIX CONTACT GmbH Co. KG | 32823 Blomberg, Germany | Phone +49-(0)5235-3-00 | Fax +49-(0)5235-3-41200 | www.phoenixcontact.com |

