

Reliability Prediction Assessment

The given failure rates refer to more than one article. For the valid articles please refer to the article list.

Device category 3 - electronical article

| - 7 | r | edi | cti | on | done | hv. | pyti0 |
|-----|---|-----|-----|----|------|-----|-------|
| | | cu | | | aone | Dy. | Pytio |

| at | 25 | °C with | 21,00 | % duty cycle |
|----|----|---------|--------|--------------|
| at | 40 | °C with | 34,25 | % duty cycle |
| at | 40 | °C with | 100,00 | % duty cycle |
| at | | °C with | | % duty cycle |
| at | | °C with | | % duty cycle |
| at | | °C with | | % duty cycle |
| | | | | |

| based on |
|----------|
| |
| |
| SN 29500 |
| |
| |
| |

| GB, GC - Ground Be | nign, Controlled |
|--------------------|------------------|

| MTTF in h | MTT |
|-------------|-----|
| | |
| - | |
| 12658227,85 | 14 |
| - | |
| - | |
| | |
| | |

| | failure rate in FIT (λ basis) |
|---|-------------------------------|
| | |
| _ | 70 |
| _ | 79 |
| | |
| ⊢ | |



Reliability Prediction Assessment

Article list

| Autiolo | from revision | Designation |
|--------------------|----------------|---|
| Article | HOIII TEVISION | Designation OPT-60DC/230AC/ 2 OPT- 5DC/230AC/ 2 |
| 2982184 2982168 | 02 | OPT-60DC/230AC/ 2 |
| 2982168 | 02 | OPT- 5DC/230AC/ 2 |
| 2967950 2982171 | 02 | OPT-24DC/230AC/ 1 |
| 2082171 | 02 | OPT-24DC/230AC/ 2 |
| 2902171 | 02 | OPT 00D0/000A0/ 2 |
| 2967963 | 02 | OPT-60DC/230AC/ 1 |
| | , | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| — | — | |
| | | |
| | | |
| | | |
| | | |
| | | |
| — | | - |
| | | |
| | | |
| | | |
| | | |
| | | |
| | - | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | <u> </u> | |
| | | |
| | | |
| | | |
| | | |
| | | |
| — | | - |
| | | |
| | | |
| | | |
| | | |
| | | |
| — | | |
| <u> </u> | | |
| | | |
| | | |
| | | |
| | | |
| — | | - |
| <u> </u> | <u> </u> | |
| | | |
| | | |
| | | |
| | | |
| \vdash | | - |
| | | |
| | | |
| | | |
| | | |
| \vdash | | |
| | | |
| | | |
| | | |
| | | |
| \vdash | | |
| \vdash | | - |
| | | |
| | | |
| | | |
| | | |
| | | |

PHOENIX CONTACT GmbH Co. KG | 32823 Blomberg, Germany | Phone +49-(0)5235-3-00 | Fax +49-(0)5235-3-41200 | www.phoenixcontact.com |

