

WST 10/35 - Warning cover

3030006

<https://www.phoenixcontact.com/us/products/3030006>



Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

Warning cover, 5-pos., for terminal widths of 10.2 mm, 12.2 mm, and 16 mm



Your advantages

- Accidental actuation of the terminal points is prevented
- Warning labels and warning covers serve to cover and identify mains terminal blocks
- The warning labels snap into the screw and actuation shafts of the relevant terminal block
- Can be isolated lengthwise and crosswise

Commercial Data

| | |
|--------------------------------------|---------------------|
| Item number | 3030006 |
| Packing unit | 1 pc |
| Minimum order quantity | 25 pc |
| Sales Key | BG20 |
| Product Key | BG2511 |
| Catalog Page | Page 155 (C-3-2019) |
| GTIN | 4046356303040 |
| Weight per Piece (including packing) | 1.493 g |
| Weight per Piece (excluding packing) | 1.43 g |
| Customs tariff number | 49119900 |
| Country of origin | PL |

WST 10/35 - Warning cover



3030006

<https://www.phoenixcontact.com/us/products/3030006>

Technical Data

Product properties

| | |
|---------------------|-------------------------|
| Product type | Labeled terminal marker |
| Number of positions | 5 |
| Pitch | 9.35 mm |
| Type | high |

Mounting

| | |
|---------------|---------|
| Mounting type | plug in |
|---------------|---------|

Material specifications

| | |
|--|--------------------------------|
| Color | yellow |
| Material | PA |
| Flammability rating according to UL 94 | V2 |
| Components | free from silicone and halogen |

Environmental and real-life conditions

Test for substances that would hinder coating with paint or varnish

| | |
|--------|-------------|
| Result | Test passed |
|--------|-------------|

UV resistance

| | |
|---------------|--------------------------------|
| Specification | ISO 4892-2:2013-03 (following) |
| Result | Test passed |
| Test duration | 96 h |

Wipe resistance of inscriptions

| | |
|---------------|-------------------------------------|
| Specification | DIN EN 61010-1 (VDE 0411-1):2011-07 |
|---------------|-------------------------------------|

Testing in a condensation changing climate in the presence of sulfur dioxide

| | |
|---------------|-------------------|
| Specification | DIN 50018:2013-05 |
| Result | Test passed |
| Climate level | AHT 1.0 S |
| Cycles | 2 |

Salt spray test

| | |
|---------------|---------------------------|
| Specification | DIN EN 60068-2-11:2000-02 |
| Result | Test passed |

Ambient conditions

| | |
|---|-------------------|
| Ambient temperature (operation) | -40 °C ... 100 °C |
| Recommended ambient temperature (storage/transport) | 23 °C |
| Recommended humidity (storage/transport) | 50 % |

Dimensions

WST 10/35 - Warning cover

3030006

<https://www.phoenixcontact.com/us/products/3030006>



| | |
|--------|---------|
| Width | 10.2 mm |
| Height | 1 mm |
| Length | 11.8 mm |
| Pitch | 9.35 mm |

Standards and regulations

| | |
|-----------------|-----------------------------|
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
|-----------------|-----------------------------|

WST 10/35 - Warning cover

3030006

<https://www.phoenixcontact.com/us/products/3030006>



Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27281107 |
| ECLASS-12.0 | 27281107 |
| ECLASS-13.0 | 27281107 |

ETIM

| | |
|----------|----------|
| ETIM 8.0 | EC001777 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 55121700 |
|-------------|----------|

Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com