

WST 4 - Warning cover

3030954

<https://www.phoenixcontact.com/us/products/3030954>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Warning cover, Strip, yellow, labeled, mounting type: plug in, for terminal block width: 6.2 mm, lettering field size: 4.5 x 5.55 mm, Number of individual labels: 5

Your advantages

- Accidental actuation of the terminal points is prevented
- Warning labels and warning covers serve to cover and identify mains terminal blocks
- The warning labels snap into the screw and actuation shafts of the relevant terminal block
- Can be isolated lengthwise and crosswise

Commercial Data

Item number	3030954
Packing unit	1 pc
Minimum order quantity	50 pc
Sales Key	BG20
Product Key	BG2511
Catalog Page	Page 155 (C-3-2019)
GTIN	4017918193119
Weight per Piece (including packing)	0.398 g
Weight per Piece (excluding packing)	0.395 g
Customs tariff number	49119900
Country of origin	PL

WST 4 - Warning cover



3030954

<https://www.phoenixcontact.com/us/products/3030954>

Technical Data

Product properties

Product type	Labeled terminal marker
Number of positions	5
Pitch	6.2 mm
Type	high

Marking

Number of individual labels	5
Number of individual labels per row	5

Mounting

Mounting type	plug in
---------------	---------

Material specifications

Color	yellow
Material	PA
Flammability rating according to UL 94	V2
Components	free from silicone and halogen

Environmental and real-life conditions

Test for substances that would hinder coating with paint or varnish

Result	Test passed
--------	-------------

UV resistance

Specification	ISO 4892-2:2013-03 (following)
Result	Test passed
Test duration	96 h

Wipe resistance of inscriptions

Specification	DIN EN 61010-1 (VDE 0411-1):2011-07
---------------	-------------------------------------

Testing in a condensation changing climate in the presence of sulfur dioxide

Specification	DIN 50018:2013-05
Result	Test passed
Climate level	AHT 1.0 S
Cycles	2

Salt spray test

Specification	DIN EN 60068-2-11:2000-02
Result	Test passed

Ambient conditions

Ambient temperature (operation)	-40 °C ... 100 °C
Recommended ambient temperature (storage/transport)	23 °C

WST 4 - Warning cover



3030954

<https://www.phoenixcontact.com/us/products/3030954>

Recommended humidity (storage/transport)	50 %
--	------

Dimensions

Width	6.2 mm
Height	1 mm
Length	4.5 mm
Pitch	6.2 mm

Standards and regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

WST 4 - Warning cover



3030954

<https://www.phoenixcontact.com/us/products/3030954>

Classifications

ECLASS

ECLASS-11.0	27281107
ECLASS-12.0	27281107
ECLASS-13.0	27281107

ETIM

ETIM 8.0	EC001777
----------	----------

UNSPSC

UNSPSC 21.0	55121700
-------------	----------

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com