

75 Ohm Type F F/F Bulkhead Coaxial RF Surge Protector, DC - 2.5GHz, 50W, IP67, 60 V Max., 10kA, Gas Discharge Tube



GT75-FFF

Features

- Surge current of 10kA
- Max Power 50W(RMS)
- Frequency range from DC to 2.5 GHz
- F-type Female connectors
- Waterproof IP67 rated
- DC Pass
- CE & RoHS compliant
- Bidirectional

Applications

- WiFi
- GPS
- Land mobile radio

Description

RF surge protector (also known as lightning arrester) GT75-FFF from PolyPhaser utilizing a proprietary gas tube surge protection technology protects critical hardware from lightening events while maintaining the RF performance. This RF surge protector component is manufactured in a coaxial in-line design with wide operating frequency range. All PolyPhaser RF surge protector products are available in stock with same day shipping.

Electrical Specifications

Surge Protector Type
DC Handling

Gas Discharge Tube
DC Pass

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		2.5	GHz
Impedance		75		Ohms
VSWR		1.1:1	1.4:1	
Insertion Loss		0.12	0.2	dB
Operating Voltage (DC)			60	Volts
Operating Current (DC)			6	A
Input Power, CW			50	Watts
Surge Current IEC 61000-4-5 8/20µs waveform (multiple)			10	kA
Turn On Voltage		300 20%		Volts

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
[75 Ohm Type F F/F Bulkhead Coaxial RF Surge Protector, DC - 2.5GHz, 50W, IP67, 60 V Max., 10kA, Gas Discharge Tube GT75-FFF](#)

75 Ohm Type F F/F Bulkhead Coaxial RF Surge Protector, DC - 2.5GHz, 50W, IP67, 60 V Max., 10kA, Gas Discharge Tube



GT75-FFF

Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency Range	DC to 1	1 to 2	2 to 2.5			GHz
VSWR, Typ	1.1:1	1.2:1	1.4:1			
Return Loss, Typ	27	20	14			dB

Mechanical Specifications

Size

Length	2.08 in [52.83 mm]
Weight	1 lbs [453.59 g]
Housing Material and Plating	Brass, Tri-Metal

Configuration

Input Connector	F Female
Output Connector	F Female

Environmental Specifications

Temperature

Operating Range	-50 to +85 deg C
-----------------	------------------

Ingress Protection (IP) Rating

IP67

Humidity

95%

Compliance Certifications

Certifications

NOM

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
[75 Ohm Type F F/F Bulkhead Coaxial RF Surge Protector, DC - 2.5GHz, 50W, IP67, 60 V Max., 10kA, Gas Discharge Tube GT75-FFF](#)

75 Ohm Type F F/F Bulkhead Coaxial RF Surge Protector, DC - 2.5GHz, 50W, IP67, 60 V Max., 10kA, Gas Discharge Tube



GT75-FFF

Plotted and Other Data

Notes:

PolyPhaser protects and increases the reliability of global RF communications networks, including transportation, telecommunications, defense, security and industrial applications, with superior RF surge protection technologies including DC Block, DC Pass and Ultra Low PIM. Backed by responsive service and expert technical support PolyPhaser continually expands its product offering and services to serve engineers' urgent needs for RF components in mission critical communication networks.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [75 Ohm Type F F/F Bulkhead Coaxial RF Surge Protector, DC - 2.5GHz, 50W, IP67, 60 V Max., 10kA, Gas Discharge Tube GT75-FFF](https://www.polyphaser.com/type-f-surge-protector-2.5ghz-2ghz-gas-discharge-tube-gt75-fff-p.aspx)

URL: <https://www.polyphaser.com/type-f-surge-protector-2.5ghz-2ghz-gas-discharge-tube-gt75-fff-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. PolyPhaser reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. PolyPhaser does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and PolyPhaser does not assume any liability arising out of the use of any part or documentation.

75 Ohm Type F F/F Bulkhead Coaxial RF Surge Protector, DC - 2.5GHz,
50W, IP67, 60 V Max., 10kA, Gas Discharge Tube

GT75-FFF CAD Drawing

