

Rittal – The System.

Faster – better – everywhere.

Enclosure Heaters with fan – SK 3105.390

Date : Dec 23, 2016

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Enclosure Heaters with fan – SK 3105.390

created: 23.12.2016 build on www.rittal.com/us-en



Product description

Supply includes: Quick-connection terminal
Fasteners

Note: For precise temperature control inside the enclosure, we recommend using the enclosure internal thermostat or the digital enclosure internal temperature display and thermostat. In order to prevent condensation on assemblies, hygostat is recommended to regulate heating. In larger enclosures, even heat distribution is best achieved by installing several low-output heaters. The installation of heaters is generally advisable, in order to prevent condensation.

Product features

Continuous thermal output at 10°C: 400 W - 415 W
Note: Continuous thermal output with fan

Rated operating voltage: 230 V, 1~, 50 Hz/60 Hz

Dimensions: Height: 200 mm (7.9 ")
Width: 103 mm (4.1 ")
Depth: 103 mm (4.1 ")

Pre-fuse: Miniature circuit-breaker/fuse: 6 A

Integrated fan: yes

Packaging unit: 1 pc(s).

Weight/packaging unit: 1.22 kg (2.7 lb.)

EAN: 4028177662872

Customs tariff number: 85162999

ETIM 6.0: EC000737

ETIM 5.0: EC000737

eCl@ss 8.0/8.1: 27180710

eCl@ss 7.0/7.1: 27180710

eCl@ss 6.0/6.1: 27180710

eCl@ss 5.1/5.1.4: 27180710

Approvals

Approvals: Approval overview
CSA
UR
UR + C-UR
VDE

Declarations: Declaration of conformity