

Faster – better – everywhere.





SK 3238.208 Outlet Filters

State: 9/22/2023 (Source: rittal.com/us-en)



POWER DISTRIBUTION >> CLIMATE CONTROL

IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

ENCLOSURES

SK 3238.208 - Outlet Filters Standard

For ventilation by convection, an outlet filter can be installed in the upper and lower sections of the enclosure.



Features

Model No.	SK 3238.208
Product description	For ventilation by convection, an outlet filter can be installed in the upper and lower sections of the enclosure.
Material	ABS
Color	RAL 9005
Supply includes	Outlet Filters
	Fleece filter mat
Mounting cut-out	Width of opening: 124 mm
	Cut-out height: 124 mm
	Width of opening: 4.88 "
	Cut-out height: 4.88 "
Dimensions	Width: 148.5 mm
	Height: 148.5 mm
	Depth: 24 mm
	Width: 5.85 ″
	Height: 5.85 [~]
	Depth: 0.94 "
Protection category NEMA	Type 12 with fleece filter/folded filter
Protection category IP to IEC 60	IP54 with fleece filter/folded filter
529	IP55 with folded filter and absorber mat
	IP56 with fleece filter/folded filter and hose-proof hood

Features

Weight/packaging unit	0.18 kg 0.4 lb.
Packaging unit	1 pc(s).
Customs tariff number	39269097
EAN	4028177663466
ETIM 7.0	EC002513
ECLASS 8.0	27180706

Approvals

Approvals	GOST UL + C-UL - FTTA UR + C-UR (recognized)
Certificates	EAC
Explanations	Declaration of conformity UK