

# Rittal – The System.

Faster – better – everywhere.



## SE 5830.680

## VX SE enclosure system

State: 8/16/2024 (Source: [rittal.com/us-en](http://rittal.com/us-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# SE 5830.680 - VX SE enclosure system IP 66/NEMA 4

Individual carbon steel enclosure with stable enclosure body, two integrated mounting levels, screw-fastened rear panel and door. Roof and sides from a single piece with roll-formed frame. Fully compatible with the VX25 baying system. Increases efficiency as side panels do not have to be mounted. High level of protection to IP 66/NEMA 4.

## Features

Model No.	SE 5830.680
Material	Housing: Carbon steel, 1.5 mm Door: Carbon steel, 2.0 mm Rear wall: carbon steel, 1.5 mm Base: Carbon steel, 1.5 mm Mounting plate: Carbon steel, 3.0 mm
Surface finish	Housing, door and rear panel: Dipcoat-primed, powder-coated on the outside, textured paint Mounting panel: Zinc-plated Base: Dipcoat-primed and powder-coated, textured paint
Color	RAL 7035
Supply includes	Housing, solid top and sides Door(s) Door hinged on the right, may be swapped to the left Mounting panel Base, gland plate(s) Rear panel, detachable Lock: 3 mm double-bit 2 punched rails, 18 x 39 mm
Dimensions	Width: 600 mm Height: 1,800 mm Depth: 400 mm Width: 23.6 " Height: 70.9 " Depth: 15.7 "
Dimensions of mounting plate (W x H)	499 mm x 1,696 mm 19.6 " x 66.8 "

# Features

---

Protection category IP to EN 60529	IP 66
------------------------------------	-------

---

Protection category NEMA	NEMA 4
--------------------------	--------

---

Type rating according to UL 50E	Type 1 Type 2 Type 3 Type 3R Type 4 Type 12
---------------------------------	--

---

IK code	IK10
---------	------

---

Number of doors	1
-----------------	---

---

Base material	Carbon steel
---------------	--------------

---

Packaging unit	1 pc(s).
----------------	----------

---

Weight/packaging unit	104 kg 229.3 lb.
-----------------------	---------------------

---

EAN	4028177959323
-----	---------------

---

ETIM 7.0	EC000261
----------	----------

---

ECLASS 8.0	27180101
------------	----------

# Approvals

---

Approvals	UL + C-UL (listed)
-----------	--------------------

---

Certificates	Surface finish Protection category
--------------	---------------------------------------

---

Explanations	Declaration of conformity Declaration of conformity UK
--------------	---