

Rittal – The System.

Faster – better – everywhere.



VX 5860.600

VX SE Floormount Enclosure

State: 8/16/2024 (Source: rittal.com/us-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



VX 5860.600 - VX SE Floormount Enclosure NEMA 12/3R

Free-standing/ Floormount sheet steel enclosure with stable enclosure body, two integral mounting levels, internally fastened rear panel and door. Roof and sides from a single piece with roll-formed frame and solid bottom.

Features

| | |
|---------------------|--|
| Model No. | VX 5860.600 |
| Product description | Free-standing/ Floormount sheet steel enclosure with stable enclosure body, two integral mounting levels, internally fastened rear panel and door. Roof and sides from a single piece with roll-formed frame and solid bottom. Enclosure widths from 1200 to 1800 mm and enclosure depths from 300 to 500 mm. Includes full width drip shield for added protection and removable bottom plugs for easy installation of accessory leg kits. |
| Material | Housing: Carbon steel, 1.5 mm Door: Carbon steel, 2.0 mm Rear wall: carbon steel, 1.5 mm Base plates: Carbon steel, 1.5 mm Mounting plate: Carbon steel, 3.0 mm |
| Surface finish | Housing, door and rear panel: Dipcoat-primed, powder-coated on the outside, textured paint Mounting panel: Zinc-plated |
| Color | RAL 7035 |
| Supply includes | Housing, solid top and sides Door(s) Right-hand door catch on single-door enclosures may be swapped to the left Mounting panel Base plate with removable floorstand kit plugs Rear panel, internally fastened Lock: 3 mm double-bit 2 punched rails, 18 x 39 mm |

Features

| | |
|--------------------------------------|--|
| Dimensions | Width: 1,200 mm Height: 1,600 mm Depth: 300 mm Width: 47.2 " Height: 63 " Depth: 11.8 " |
| Dimensions of mounting plate (W x H) | 1,099 mm x 1,496 mm 43.3 " x 58.9 " |
| Installation depth | 256 mm 10.1 " |
| Protection category IP to EN 60 529 | IP 55 |
| Protection category NEMA | NEMA 12 |
| Type rating according to UL 50E | Type 1 Type 2 Type 3 Type 3R Type 12 |
| IK code | IK10 |
| Number of doors | 2 |
| Packaging unit | 1 pc(s). |
| Weight/packaging unit | 169 kg 372.6 lb. |
| UPC-Code | 93692 |
