

Faster – better – everywhere.





DK 7030.111 CMC III Sensors

State: 9/22/2023 (Source: rittal.com/us-en)



POWER DISTRIBUTION CLIMATE CONTROL

IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

ENCLOSURES

DK 7030.111 - CMC III Sensors

CMC III temperature/humidity sensor



Features

Model No.	DK 7030.111
Version	Temperature/humidity sensor
Product description	CMC III sensors are used to monitor the physical environment and can be directly connected to the PU by an RJ45 CAN bus connection cable. The sensors can also be interconnected as a bus.
Benefits	Fast connection and automatic detection via plug & play Power is supplied via the CAN bus interface.
Applications	Enclosure monitoring in IT, industry and facility management Monitoring enclosures, rooms and containers in the field of IT.
Function principle	Settings can be made via the CMC III Processing Unit or the IoT interface. The CMC III temperature/humidity sensor monitors the ambient temperature and air humidity in the enclosure. The sensor has an integrated temperature sensor and an integrated air humidity sensor.
Material	Plastic Front: Smooth Housing: Textured
Color	Front: RAL 9005 Housing: RAL 7035
Supply includes	Sensor Mounting plate Assembly components Temperature/humidity sensor

Features

Direct
2 x RJ45 CAN bus
32
4
32
16
Temperature Sensor Chip Humidity Sensor Chip
Width: 80 mm Height: 30 mm Depth: 40 mm Width: 3.15 " Height: 1.18 " Depth: 1.57 "
0 °C55 °C 32 °F131 °F
595 %
1 pc(s).
0.206 kg 0.5 lb.
90268020
4028177659490
EC002627
27189253

Approvals

Approvals

Approvals	UL + C-UL (listed)
Certificates	EAC
Explanations	Manufacturer's declaration Declaration of conformity