

Faster – better – everywhere.





WM wall-mounted enclosure

CLIMATE CONTROL

IT INFRASTRUCTURE SOFTWARE & SERVICES

State: 8/16/2024 (Source: rittal.com/us-en)

POWER DISTRIBUTION



FRIEDHELM LOH GROUP

ENCLOSURES

WM 8018.552 - WM wall-mounted enclosure 316 stainless steel

These single door wallmount enclosures can be used for virtually any application. The WM series ensures NEMA protection through a secure locking system, foamed-in-place gasket, and knife-edge sealing surface. Features include a stainless steel 316L body and door, and a zinc plated mounting panel.



Features

Model No.	WM 8018.552
Material	Door: Stainless steel, all-round foamed-in PU seal
	Stainless steel 1.4404 (AISI 316L)
	Mounting plate: Carbon steel, zinc-plated
Surface finish	Brushed
Supply includes	Housing with door(s)
	Door hinged on left
	Mounting plate
	Wall mounting blind-nuts
Dimensions	Width: 760 mm
	Height: 900 mm
	Depth: 250 mm
	Width: 29.9 "
	Height: 35.4 ″
	Depth: 9.84 "
Dimensions of mounting plate (W	704 mm x 870 mm
x H)	27.7 [~] x 34.3 [~]
Protection category NEMA	NEMA 4X

Features

Packaging unit	1 pc(s).
Customs tariff number	7326909099
UPC-Code	83574

Approvals

Approvals

Explanations

UL + C-UL (listed)

Declaration of conformity