

Rittal – The System.

Faster – better – everywhere.



WM 8018.633

WM wall-mounted disconnect enclosure

State: 8/16/2024 (Source: rittal.com/us-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



WM 8018.633 - WM wall-mounted disconnect enclosure 304 stainless steel

These flange mount disconnect wallmount enclosures can be used for virtually any application. The WM series ensures NEMA protection through a secure locking system, foamed-in-place gasket, and knife-edge sealing surface. Features include a stainless steel body and door, and a zinc plated mounting panel.



Features

Model No.	WM 8018.633
Material	Door: Stainless steel, all-round foamed-in PU seal Housing and door: Stainless steel 1.4301 (AISI 304) Mounting plate: Carbon steel, zinc-plated
Surface finish	Brushed
Supply includes	Housing with door Door hinged on left Wall mounting blind-nuts Flange door with universal disconnect cutout
Dimensions	Width: 825 mm Height: 900 mm Depth: 300 mm Width: 32.5 " Height: 35.4 " Depth: 11.8 "
Dimensions of mounting plate (W x H)	704 mm x 870 mm 27.7 " x 34.3 "
Protection category NEMA	NEMA 4X

Features

Material thickness - door	2 mm 0.08 "
---------------------------	----------------

Material thickness - enclosure	2 mm 0.08 "
--------------------------------	----------------

Material thickness – mounting plate	3 mm 0.12 "
-------------------------------------	----------------

Packaging unit	1 pc(s).
----------------	----------

Weight/packaging unit	56 kg 123.5 lb.
-----------------------	--------------------

Customs tariff number	7326909099
-----------------------	------------

UPC-Code	83951
----------	-------

Approvals

Explanations

Declaration of conformity