

IO module, Expansion Modules, 16 DI, 6 AI, 8CI, 8 DO

TBUX297583S

Product availability: Stock - Normally stocked in distribution facility

Main

Range of Product	Expansion Modules
Product or Component Type	I/O module
Range Compatibility	SCADAPack 47x SCADAPack 57x SCADAPack 500E

Complementary

Complementary	
Input type	Digital x16 Analog x6 Counter x8
Analogue input type	Voltage 05 V Voltage 15 V Current 020 mA Current 420 mA
Output type	8 digital
Power consumption in W	1.1 W
Length	1.76 in (44.7 mm)
Width	5.93 in (150.5 mm)
Height	7.18 in (182.3 mm)

Environment

Marking	CE RCM
Product Certifications	CE CSA UL
Standards	FCC CFR 47 part 15, Subpart B ICES-003 UL 61010-2-201 UL 61010-1 CSA C22.2 No 61010-1 CSA C22.2 No 61010-1-12 IEC 61131-2
Pollution degree	2
Relative humidity	595 %
Ambient Air Temperature for Storage	-40185 °F (-4085 °C) -40185 °F (-4085 °C)
Ambient Air Temperature for Operation	-40158 °F (-4070 °C) -40316 °F (-40158 °C)

Ordering and shipping details

Category	18277-TELEMETRY SCADAPAK COMPACT RTU
Discount Schedule	TRSS
GTIN	3606489645175
Returnability	No
Country of origin	CA

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.85 in (4.71 cm)
Package 1 Width	7.18 in (18.23 cm)
Package 1 Length	5.93 in (15.05 cm)
Package 1 Weight	1.87 lb(US) (0.85 kg)
Unit Type of Package 2	BB1
Number of Units in Package 2	1
Package 2 Height	2.50 in (6.35 cm)
Package 2 Width	10.00 in (25.4 cm)
Package 2 Length	9.00 in (22.86 cm)
Package 2 Weight	29.98 oz (850 g)
Unit Type of Package 3	S03
Number of Units in Package 3	6
Package 3 Height	11.81 in (30 cm)
Package 3 Width	11.81 in (30 cm)
Package 3 Length	15.75 in (40 cm)
Package 3 Weight	14.55 lb(US) (6.6 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration
RoHS exemption information	Yes
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Recommended replacement(s)