

Current sensor relay, SE Relays, SPDT, 15A, 24 to 240 VAC, 1 time scale, 800 mA to 8 A, DIN mounting

841CS8-UNI

Product availability: Non-Stock - Not normally stocked in

distribution facility

Price\*: 144.72 USD

#### Main

Product Range	Legacy
Sensory Type	Current sensor
Product Or Component Type	Relay
Switch Function	SPDT
Contacts Material	AgNi
Time Delay Type	Adjustable
Rated Supply Voltage	24240 V AC 5060 Hz

### Complementary

Time Delay Range	010 s
Control Type	With adjustment knob front
Nominal Output Current	15 A
Local Signalling	1 LED red 1 LED green
Repeat Accuracy	+/- 1 %
Tripping Threshold	0.88 A
Temperature Drift	< 0.1 %/°C
Power Consumption In Va	1.5 VA 24240 V
Rated Operational Current	15 A at 240 V AC-1
Breaking Capacity	4000 VA AC-1
Motor Power Hp	0.5 hp 120 V AC 1 hp 240 V
Minimum Switching Current	100 mA 5 V
Maximum Switching Voltage	250 V
Tightening Torque	7.08 lbf.in (0.8 N.m)
Awg Gauge	AWG 14
Electrical Durability	30000 cycles
Mechanical Durability	15000000 cycles
Mounting Support	35 mm DIN rail conforming to IEC 60715
Overvoltage Category	III IEC 60664-1
Height	3.54 in (90 mm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Width	0.69 in (17.6 mm)
Depth	2.52 in (64 mm)
Product Weight	2.22 oz (63 g)

### **Environment**

Dielectric Strength	4000 V between input and output
Standards	IEC 61010-1 EN 60255-26 EN 60255-27
Product Certifications	UL CE WEEE RoHS
Ambient Air Temperature For Storage	-22158 °F (-3070 °C)
Ambient Air Temperature For Operation	-4131 °F (-2055 °C)
Ip Degree Of Protection	IP20 IEC 60529 terminals) IP40 IEC 60529 front panel)

## Ordering and shipping details

Category	21127-ZELIO ICE CUBE RELAYS
Discount Schedule	CP2
Gtin	3606480282102
Returnability	Yes
Country Of Origin	CZ

# **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	0.80 in (2.03 cm)
Package 1 Width	3.80 in (9.65 cm)
Package 1 Length	3.60 in (9.14 cm)
Package 1 Weight	0.15 lb(US) (0.07 kg)
Unit Type Of Package 2	CAR
Number Of Units In Package 2	10
Package 2 Height	2.95 in (7.5 cm)
Package 2 Width	3.94 in (10 cm)
Package 2 Length	8.74 in (22.2 cm)
Package 2 Weight	1.54 lb(US) (0.7 kg)

### Sustainability

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

### Well-being performance

Reach Free Of Svhc	
Toxic Heavy Metal Free	
Mercury Free	
Rohs Exemption Information	Yes
Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
California Proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

**Dimensions Drawings** 

#### **Dimensions**

