



Power Relay, Type C, 2 HP, 30A resistive at 300 VAC, DPDT, 2 normally open and 2 normally closed contact, 12 VDC coil

8501CDO16V51

Product availability: Stock - Normally stocked in distribution facility

Price\*: 128.10 USD

### Main

product range	Power Relay 8501C
product type	Power relay
short name	type C
[In] rated line current	30 A
device application	Suited for controlling small single phase motors and other light loads
switch function	DPDT
contact composition	2 NO/2 NC
[Uc] control circuit voltage	12 V DC
horsepower rating	2.0 hp
maximum switching voltage	600 V AC

### Complementary

class number	8501
phase	1 phase
terminal connects	Screw clamp terminal
wire range	AWG 10 copper
terminal tightening torque	1115 lbf.in (1.21.7 N.m)
coil burden	2 W
mounting	Panel mounting

#### **Environment**

ambient temperature range - operational	-3060 °C (-22140 °F)
product certifications	UL listed file E78351 CCN NLDX CSA CE
height	3.12 in (79.25 mm)
width	2.5 in (63.5 mm)
depth	2.31 in (58.67 mm)

# Ordering and shipping details

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Category	US10CP221131
Discount Schedule	0CP2
GTIN	785901052180
Returnability	Yes
Country of origin	CN

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.50 in (6.35 cm)
Package 1 Width	2.60 in (6.604 cm)
Package 1 Length	3.20 in (8.128 cm)
Package 1 Weight	7.84 oz (222.26 g)

# **Contractual warranty**

Warranty 18 months

## Sustainability

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

How we assess product sustainability >



Transparency

## Well-being performance

<b>⊘</b>	Reach Free Of Svhc	
<b>②</b>	Toxic Heavy Metal Free	
	Mercury Free	
<b>②</b>	Rohs Exemption Information	Yes
Rea	ch Regulation	REACh Declaration
Eu	Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Chi	na Rohs Regulation	China RoHS declaration
Env	ironmental Disclosure	Product Environmental Profile
Circ	cularity Profile	No need of specific recycling operations
Cali	fornia Proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov