

# 8501XB40

NEMA Control Relay, Type X, adder deck, 10A resistive at 600 VAC, 4 normally open contacts

Product availability : Stock - Normally stocked in distribution facility



Price\* : 98.00 USD



## Main

|                           |               |
|---------------------------|---------------|
| Range of product          | 8501X         |
| Relay type                | Control relay |
| Product or component type | Adder deck    |

## Complementary

|   |   |
|---|---|
| Rated breaking capacity                   | 6 A 120 V AC inductive control circuit UL 508<br>3 A 240 V AC inductive control circuit UL 508<br>1.5 A 480 V AC inductive control circuit UL 508<br>1.2 A 600 V AC inductive control circuit UL 508<br>10 A <= 600 V AC resistive control circuit UL 508<br>1.1 A 125 V DC inductive control circuit UL 508<br>0.55 A 250 V DC inductive control circuit UL 508<br>0.2 A 301...600 V DC inductive control circuit UL 508<br>4 A 125 V DC resistive control circuit UL 508<br>0.8 A 250 V DC resistive control circuit UL 508 |
| [Icm] rated short-circuit making capacity | 60 A 120 V AC inductive control circuit UL 508<br>30 A 240 V AC inductive control circuit UL 508<br>15 A 480 V AC inductive control circuit UL 508<br>12 A 600 V AC inductive control circuit UL 508<br>10 A <= 600 V AC resistive control circuit UL 508<br>1.1 A 125 V DC inductive control circuit UL 508<br>0.55 A 250 V DC inductive control circuit UL 508<br>0.2 A 301...600 V DC inductive control circuit UL 508<br>4 A 125 V DC inductive control circuit UL 508<br>0.8 A 250 V DC resistive control circuit UL 508 |
| Contacts Configuration                    | 4 NO 4 standard contact cartridges  |
| Electrical connection                     | Screw clamp terminals   |
| Wire Gauge                                | AWG 18...AWG 12 copper  |
| Terminal Tightening Torque                | Control circuit 9.03...12.04 lbf.in (1.02...1.36 N.m) screw terminals   |

\* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

## Environment

|                        |   |
|------------------------|---|
| Product certifications | CE<br>CSA LR60905 class 3211 02<br>UL recognized E78403 CCN NKCR2 |
|------------------------|---|

## Ordering and shipping details

|                       |                            |
|-----------------------|----------------------------|
| Category              | 21159 - 8501 X ACCESSORIES |
| Discount Schedule     | CP2                        |
| GTIN                  | 00785901537328             |
| Nbr. of units in pkg. | 1                          |
| Package weight(Lbs)   | 0.55 lb(US) (0.25 kg)      |
| Returnability         | Yes                        |
| Country of origin     | MX                         |

## Packing Units

|                        |                      |
|------------------------|----------------------|
| Unit Type of Package 1 | PCE                  |
| Package 1 Height       | 7.62 in (19.355 cm)  |
| Package 1 width        | 3.00 in (7.62 cm)    |
| Package 1 Length       | 19.35 in (49.161 cm) |

## Offer Sustainability

|                            |  |
|----------------------------|--|
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)<br><a href="#">EU RoHS Declaration</a>                      |
| Mercury free               | Yes  |
| RoHS exemption information | <a href="#">Yes</a>  |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a><br>Product out of China RoHS scope. Substance declaration for your information. |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>  |
| Circularity Profile        | <a href="#">End of Life Information</a>  |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|