Product data sheet Characteristics

8501XMO40V02

NEMA Control Relay, Type X, master, 10A resistive at 600 VAC, 4 normally open contacts, 110/120 VAC 50/60 Hz coil

Product availability: Stock - Normally stocked in distribution facility





Price*: 336.00 USD



Main

Main		
Range	8501X	
Relay Type	Master	7
Product	Relay	in distribution of the state of
Current Rating	20 A AC	- 9
Contact Configuration	4 NO 4 master contact cartridges	eu ira Historia Historia
Number of Poles	4P	: <u>:</u> 0
Coil Voltage	110 V AC 50 Hz 120 V AC 60 Hz	- de formula in
Voltage Rating	600 V AC	
Mounting Type	Panel	d
Operating Temperature	-40160 °F (-4071 °C)	
Electrical Connection	Screw clamp terminals	÷
Certifications	CE UL Listed CSA	to for and is
Operating Time	15 ms - pick-up 16 ms - drop-out	u crh crh eti
		"

Ordering and shipping details

0 11 0	5000-000A-000A	
Category	21158 - 8501 XO (AC)	to u
Discount Schedule	CP2	igi igi
GTIN	00785901743446	en
Nbr. of units in pkg.	1	
Package weight(Lbs)	2.1 lb(US) (0.95 kg)	
Returnability	Yes	

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.





Country of origin	MX	
Packing Units		
Unit Type of Package 1	PCE	
Package 1 Height	8.89 in (22.581 cm)	
Package 1 width	3.50 in (8.89 cm)	
Package 1 Length	22.58 in (57.355 cm)	
Offer Sustainability Sustainable offer status	Green Premium product	
Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
	China RoHS declaration	
China RoHS Regulation	China Norte decidation	
China RoHS Regulation Environmental Disclosure	Product Environmental Profile	

18 months

Contractual warranty

Warranty