Product data sheet Characteristics

8501XMO60V02

NEMA Control Relay, Type X, master, 10A resistive at 600 VAC, 6 normally open contacts, 110/120 VAC 50/60 Hz coil

Product availability: Stock - Normally stocked in distribution facility



Price*: 457.00 USD



Main

Main		
Range	8501X	
Relay Type	Master	
Product	Relay	
Current Rating	20 A AC	
Contact Configuration	6 NO 6 master contact cartridges	
Number of Poles	6P	
Coil Voltage	110 V AC 50 Hz 120 V AC 60 Hz	
Voltage Rating	600 V AC	
Mounting Type	Panel	
Operating Temperature	-40160 °F (-4071 °C)	
Electrical Connection	Screw clamp terminals	
Certifications	CSA UL Listed CE	
Operating Time	15 ms - pick-up 16 ms - drop-out	

Ordering and shipping details

0 11 0	300-300-300	
Category	21158 - 8501 XO (AC)	
Discount Schedule	CP2	
GTIN	00785901018247	
Nbr. of units in pkg.	1	
Package weight(Lbs)	2.39 lb(US) (1.08 kg)	
Returnability	Yes	

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.



Country of origin	MX	
Packing Units		
Package 1 Height	2.54 in (6.452 cm)	
Package 1 width	1.00 in (2.540 cm)	
Package 1 Length	6.45 in (16.387 cm)	
Offer Sustainability		
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End of Life Information	

18 months

Warranty

