Product data sheet Characteristics

8501XUDO40V63Y414

NEMA Control Relay, Type X, utility, 10A resistive at 600 VAC, 4 normally open contacts, 125 VDC coil, pan head screws

Product availability: Non-Stock - Not normally stocked in distribution facility





Price*: 390.00 USD



Main

Mairi		
Range	8501X	
Relay Type	Utility	75
Product	Relay	
Current Rating	10 A AC 5 A DC	ility or r
Contact Configuration	4 NO 4 standard contact cartridges	<u> </u>
Number of Poles	4P	
Coil Voltage	125 V DC	<u> </u>
Voltage Rating	250 V DC	
Mounting Type	Panel	
Operating Temperature	-40160 °F (-4071 °C)	
Electrical Connection	Ring tongue	±
Certifications	UL Listed CE CSA	to for and is
Operating Time	37 ms - pick-up 21 ms - drop-out	s dibatit

Ordering and shipping details

0 11 0		
Category	21157 - 8501 XDO (DC)	
Discount Schedule	CP2	
GTIN	00785901743576	
Nbr. of units in pkg.	1	
Package weight(Lbs)	3.36 lb(US) (1.52 kg)	
Returnability	No	

^{*} Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.





Country of origin	MX	
Offer Sustainability		
Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End of Life Information	

Contractual warranty

Warranty	18 months	