Product data sheet Characteristics

8536SBW12V03A

Non-Reversing Starter Size 0, 3-Pole, Melting Alloy Overload, NEMA 4/4X +Options

Product availability: Non-Stock - Not normally stocked in distribution facility



Price*: 1,353.00 USD



Main

Product or component type	Starter	
Туре	S	
Control Circuit Type	Common control circuit	•

Complementary		
Control Circuit Voltage	220 V AC 50 Hz 240 V AC 60 Hz	
Motor starter type	Non reversing	-
Current Rating	18 A	
Number of Poles	3P	
Number of Phases	3 phase	
Horsepower Rating	3 HP 200 V AC 3 HP 230 V AC 5 HP 460 V AC 5 HP 575 V AC	
Maximum Voltage Rating	600 V AC	
Control Units	2 momentary push-buttons (START-STOP)	
Thermal overload type	Melting alloy 3	
Electrical connection	Screw clamp terminals	
NEMA size	0	
Maximum Height	13.19 in (335 mm)	
Maximum Depth	7.80 in (198 mm)	
Maximum Width	6.38 in (162 mm)	

Environment

Enclosure Type NEMA	4/4X brushed stainless steel
---------------------	------------------------------

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.





Product certifications	UL Listed CSA NEMA
Ordering and shipping details	
Category	21203 - 8502,36 W/STAINLESS ENCLOSURES

CP1

No

00785901904618

Country of origin	MX	
Offer Sustainability		
FU RoHS Directive	Not compliant	

China RoHS declaration
Product out of China RoHS scope. Substance declaration for your information.

Contractual warranty

China RoHS Regulation

Discount Schedule

GTIN

Returnability

Contractual warranty		
Warranty	18 months	