Product data sheet Characteristics

8536SCA2V02S

Non-Reversing Starter Size 1P, 2-Pole, Melting Alloy Overload, NEMA 12 +Options

Product availability: Non-Stock - Not normally stocked in distribution facility



Price*: 867.00 USD



Main

Product or component type	Starter	
Туре	S	
Control Circuit Type	Separate control circuit	

Complementary

Complementary		ō
Control Circuit Voltage	110 V AC 50 Hz 120 V AC 60 Hz	
Motor starter type	Non reversing	
Current Rating	27 A	į
Number of Poles	2P	Ş
Number of Phases	1 phase	
Horsepower Rating	3 HP 115 V AC 5 HP 230 V AC	\$ 5
Maximum Voltage Rating	600 V AC	
Control Units	No control units	, j
Thermal overload type	Melting alloy 1	d. Parkiti
Electrical connection	Screw clamp terminals	
NEMA size	1P	0
Maximum Height	12.76 in (324 mm)	
Maximum Depth	8.54 in (217 mm)	ق
Maximum Width	6.38 in (162 mm)	

Environment

Environment		
Enclosure Type	NEMA 12 painted sheet steel	ة. - ح
Product certifications	UL Listed	ŗ

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.







Ordering and shipping details

Category	21192 - 8502,36 SC,SD(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901019046
Nbr. of units in pkg.	1
Package weight(Lbs)	16.24 lb(US) (7.37 kg)
Returnability	No
Country of origin	MX

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Not compliant	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.	
PVC free	Yes	

Contractual warranty

Warranty	18 months