

Product data sheet

Characteristics

8903LXO1000V03

Contacteur, Type L, multipole lighting, mechanically held, 30A, 10 pole, 600 V, 220/240 VAC 50/60 Hz coil, open style



Main

Product or Component Type	Mechanically Held Lighting Contactor
---------------------------	--------------------------------------

Complementary

Height	8.81 in (223.77 mm)
Depth	3.25 in (82.55 mm)
Width	5.63 in (143.002 mm)

Environment

Product Certifications	UL listed file E78427 CCN NRNT
------------------------	--------------------------------

Ordering and shipping details

Category	US10CP121322
Discount Schedule	0CP1
GTIN	785901808107
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.0000000000 in (10.16 cm)
Package 1 Width	7.50 in (19.05 cm)
Package 1 Length	10.50 in (26.67 cm)
Package 1 Weight	9.374 lb(US) (4.252 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes

China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

Contractual warranty

Warranty	18 months
----------	-----------