



Contactor, Type L, multipole lighting, mechanically held, 30A, 2 pole, 600 V, 110/120 VAC 50/60 Hz coil, open style

8903LXO20V02

Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 590.00 USD

### Main

| Product or Component Type | Mechanically Held Lighting Contactor |  |
|---------------------------|--------------------------------------|--|
| Range of Product          | 8903LX                               |  |
| Control Circuit           | Separate control circuit             |  |

### Complementary

| oompromontar.         | ,  |  |
|-----------------------|--|--|
| Control Voltage       | 110 V AC 50 Hz<br>120 V AC 60 Hz               |  |
| Inrush power in VA    | 150 VA 60 Hz<br>140 VA 50 Hz<br>25 VA 50/60 Hz |  |
| Current Rating        | 20 A tungsten<br>30 A fluorescent              |  |
| Number of Poles       | 2P 2 NO  |  |
| Control Unit          | No control units                               |  |
| Pilot Light           | No indicator                                   |  |
| Other Options         | None   |  |
| Electrical Connection | Screw-clamp terminals                          |  |
| Height                | 8.8 in (224 mm)                                |  |
| Depth                 | 3.3 in (83 mm)                                 |  |
| Width                 | 2.9 in (73 mm)                                 |  |
|                       |  |  |

#### **Environment**

| Enclosure Type         | Not rated (open device) |  |
|------------------------|-------------------------|--|
| Product Certifications | UL Listed<br>CSA        |  |

# Ordering and shipping details

| Category          | US10CP121322 |  |
|-------------------|--------------|--|
| Discount Schedule | 0CP1         |  |
| GTIN              | 785901057239 |  |
| Returnability     | Yes          |  |
| Country of origin | MX           |  |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

# **Packing Units**

| Unit Type of Package 1       | PCE                     |
|------------------------------|-------------------------|
| Number of Units in Package 1 | 1                       |
| Package 1 Height             | 4.50 in (11.43 cm)      |
| Package 1 Width              | 7.40 in (18.796 cm)     |
| Package 1 Length             | 10.50 in (26.67 cm)     |
| Package 1 Weight             | 4.601 lb(US) (2.087 kg) |

# **Contractual warranty**

Warranty 18 months

Nov 18, 2024

## **Sustainability**

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

How we assess product sustainability >



Transparency

## Well-being performance

| Reach Free Of Svhc          |   |
|-----------------------------|---|
| Toxic Heavy Metal Free      |   |
| Mercury Free                |   |
| Rohs Exemption Information  | Yes   |
| Halogen Content Performance | Halogen free plastic parts product  |
| Pvc Free                    | Yes   |
|                             |   |
| Reach Regulation            | REACh Declaration   |
| Eu Rohs Directive           | Compliant EU RoHS Declaration   |
| China Rohs Regulation       | China RoHS declaration  Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Environmental Disclosure    | Product Environmental Profile   |
| Circularity Profile         | No need of specific recycling operations  |
| California Proposition 65   | WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov                            |