

# Product data sheet

## Characteristics

# 8903LXO40V04

8903LX mechanically held lighting contactor, 4 P, 4 NO, 30 A, 600 V, 277 V 60 Hz coil, open

Product availability : Non-Stock - Not normally stocked in distribution facility



Price\* : 647.00 USD



### Main

Product or component type	Mechanically Held Lighting Contactor
Range of product	8903LX
Control Circuit	Separate control circuit

### Complementary

Control Voltage	277 V AC 60 Hz
Inrush power in VA	150 VA 60 Hz 150 VA 50/60 Hz
Current Rating	20 A tungsten 30 A fluorescent
Number of Poles	4P 4 NO
Control Unit	No control units
Pilot Light	No indicator
Other Options	None
Electrical connection	Screw-clamp terminals
Maximum Height	8.82 in (224 mm)
Maximum Depth	3.27 in (83 mm)
Maximum Width	2.87 in (73 mm)

### Environment

Enclosure Type	Not rated (open device)
Product certifications	UL Listed CSA

\* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

### Ordering and shipping details

Category	21322 - 8903 LX (NOT L)
Discount Schedule	CP1
GTIN	00785901057338
Returnability	No
Country of origin	MX

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

### Contractual warranty

Warranty	18 months
----------	-----------