

Product data sheet

Characteristics

8903SPO2V03

Contacteur, Type S, multipole lighting, electrically held, 60A, 3 pole, 220/240 VAC 50/60 Hz coil, open style

Product availability : Non-Stock - Not normally stocked in distribution facility



Price* : 890.00 USD



Main

Product	Electrically Held Lighting Contactor
Type	S

Complementary

Control Circuit Voltage	240 V AC 60 Hz 220 V AC 50 Hz
Current Rating	60 A
Number of Poles	3P
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Without
Other Options	None
Electrical connection	Lugs
Maximum Height	5.51 in (140 mm)
Maximum Depth	4.92 in (125 mm)
Maximum Width	4.33 in (110 mm)

Environment

Enclosure Type	Not rated (open device) surface none
Product certifications	UL Listed CSA

* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Ordering and shipping details

Category	21325 - 8903 S (NOT S*C) ELECT.
Discount Schedule	CP1
GTIN	00785901862246
Returnability	No
Country of origin	MX

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.

Contractual warranty

Warranty	18 months
----------	-----------