

Product data sheet

Characteristics

8910DPA72RV09

Contacteur, Definite Purpose, 75A, 2 pole, 15 HP at 230 VAC, 1 phase, 208/240 VAC 60 Hz
220 VAC 50 Hz coil, open

Main

| | |
|---------------------------|----------------------------|
| Product or Component Type | Definite Purpose Contactor |
| Line Rated Current | 75 A |
| Number of Poles | 2P |
| Pole contact composition | 2 NO |
| Range of Product | DPA |

Complementary

| | |
|--------------------------------|--|
| Maximum Horse Power Rating | 5 Hp 115 V AC, 1 phase 15 hp 230 V AC, 1 phase |
| Locked rotor rated current | 450 A 277 V AC 375 A 460 V AC 300 A 575 V AC |
| [Ue] rated operational voltage | 600 V AC |
| [Uc] control circuit voltage | 208...240 V AC 60 Hz 220 V AC 50 Hz |
| Phase | 1 phase |
| Electrical Connection | Quick connect terminals Box lugs |
| Height | 3.7 in (92.8 mm) |
| Width | 4.10 in (104.03 mm) |
| Depth | 2.6 in (65 mm) |

Environment

| | |
|------------------------|--------------------------|
| Product Certifications | UL Recognized[RETURN]CSA |
|------------------------|--------------------------|

Ordering and shipping details

| | |
|-------------------|--------------|
| Category | US1CP1B21347 |
| Discount Schedule | CP1B |
| GTIN | 785901768289 |
| Returnability | Yes |
| Country of origin | CN |

Packing Units

| | |
|------------------------------|-----------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 2.600 in (6.604 cm) |
| Package 1 Width | 3.800 in (9.652 cm) |
| Package 1 Length | 4.600 in (11.684 cm) |
| Package 1 Weight | 22.080 oz (625.964 g) |

Offer Sustainability

| | |
|----------------------------|--|
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant with Exemptions |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|