Product data sheet Characteristics

8940XC4S2V06H30

Well-Guard Pump Panel Size 1, Motor Logic SSOLR, 480 VAC, NEMA 3R +Options

Product availability: Non-Stock - Not normally stocked in distribution facility



Price*: 2,355.00 USD



Main

Product	Well-Guard Control	-
Туре	S2	
Device application	Pumping	-

Complementary

Complementary		
Control Circuit Type	Common control circuit	
Control Circuit Voltage	480 V AC 60 Hz 440 V AC 50 Hz	
Line Rated Current	27 A	
Number of Poles	3	-
Horsepower Rating	10 hp 480 V AC, 3 phase	
Maximum Voltage Rating	600 V AC	<u> </u>
Control Units	Selector switch HAND-OFF-AUTO)	
Disconnect Type	Associated circuit breaker	7
Circuit breaker CT rating	30 A	<u>.</u>
Circuit breaker type	HLL	
Thermal overload type	Motor Logic solid state class 10/20	-
Protection type	Overload Phase loss Phase unbalance	7
Device mounting	Surface	
Electrical connection	Screw terminal	
NEMA size	1	
Maximum Height	38.50 in (978 mm)	
Maximum Width	20.43 in (519 mm)	
Maximum Depth	9.41 in (239 mm)	

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.





Environment

NEMA Rating	NEMA 3R
Enclosure type	Weatherproof enclosure indoor/outdoor
Product certifications	UL Listed NEMA

Ordering and shipping details

Category	21395 - 8940 XC,XD
Discount Schedule	CP1
GTIN	00785901973393
Returnability	No
Country of origin	MX

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
EU RoHS Directive	Under investigation
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.

Contractual warranty

Warranty	18 months		