

Main

| | |
|----------------------------|---|
| Product or Component Type | Reversing Hoist Contactor |
| Line Rated Current | 40 A |
| Maximum Horse Power Rating | 3 Hp 115 V AC, 1 phase 7.5 Hp 230 V AC, 1 phase 15 Hp 230 V AC, 3 phase 20 Hp 460 V AC, 3 phase 20 hp 575 V AC, 3 phase |

Complementary

| | |
|--------------------------------|----------------------|
| Product Certifications | UL Listed[RETURN]CSA |
| [Ue] rated operational voltage | 600 V AC |
| Poles description | 3P |
| [Uc] control circuit voltage | 24 V AC 50/60 Hz |
| Phase | 3 phase |
| Range of Product | DPR |



Ordering and shipping details

| | |
|-------------------|--------------|
| Category | US10CP121403 |
| Discount Schedule | 0CP1 |
| GTIN | 785901571568 |
| Returnability | No |
| Country of origin | CN |

Packing Units

| | |
|------------------------------|----------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 5.0000000000 in (12.7 cm) |
| Package 1 Width | 5.0000000000 in (12.7 cm) |
| Package 1 Length | 6.0000000000 in (15.24 cm) |
| Package 1 Weight | 31.999 oz (907.185 g) |

Offer Sustainability

| | |
|----------------------------|--|
| REACH Regulation |  REACH Declaration |
| EU RoHS Directive | Compliant with Exemptions |
| Mercury free | Yes |
| China RoHS Regulation |  China RoHS Declaration |
| RoHS exemption information |  Yes |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|