8965DPR44V02

Contactor, Type L, hositing, mechanically held, latch attachment, 24VAC 60 Hz coil

Main	
Product or Component Type	Reversing Hoist Contactor
Line Rated Current	40 A
Maximum Horse Power Rating	10 Hp 230 V AC, 3 phase 3 Hp 115 V AC, 1 phase 7.5 Hp 230 V AC, 1 phase 20 Hp 460 V AC, 3 phase 20 hp 575 V AC, 3 phase

Complementary

Product Certifications	UL Listed[RETURN]CSA
[Ue] rated operational voltage	600 V AC
Poles description	4P
[Uc] control circuit voltage	110 V AC 50 Hz 120 V AC 60 Hz
Phase	3 phase
Range of Product	DPR

Ordering and shipping details

Category	US10CP121403
Discount Schedule	0CP1
GTIN	785901168959
Returnability	No
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.000000000 in (12.7 cm)
Package 1 Width	5.000000000 in (12.7 cm)
Package 1 Length	7.400 in (18.796 cm)
Package 1 Weight	3.999 lb(US) (1.814 kg)

Offer Sustainability

REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Compliant with Exemptions	
Mercury free	Yes	
China RoHS Regulation	☑ China RoHS Declaration	
RoHS exemption information	₽¥Yes	

Contractual warranty

Warranty	18 months