Product data sheet Characteristics

9001SKT38LRR9 PILOT LIGHT 120V 30MM SK +OPTIONS

Product availability: Stock - Normally stocked in distribution facility





Price*: 197.00 USD



Main

2010 (1970A-0)		
Lens type	Domed plastic	
Light block supply	Direct 120 V	

Complementary

Bezel material	Plastic
Mounting diameter	1.18 in (30 mm)
Shape of signaling unit head	Round
Light source	Red LED
Operating mode	Push-to-test

Environment

Protective treatment	TC
IP degree of protection	IP66

Ordering and shipping details

Main		
Lens type	Domed plastic	
Light block supply	Direct 120 V	
Complementary		
Bezel material	Plastic	
Mounting diameter	1.18 in (30 mm)	
Shape of signaling unit head	Round	
	Red LED	
Light source	Red LED Push-to-test	
Light source		
Light source Operating mode Environment		
Light source Operating mode		
Light source Operating mode Environment Protective treatment	Push-to-test	
Light source Operating mode Environment Protective treatment	Push-to-test TC	
Light source Operating mode Environment Protective treatment IP degree of protection	TC IP66	
Light source Operating mode Environment Protective treatment IP degree of protection Ordering and shipping details	Push-to-test TC IP66	
Light source Operating mode Environment Protective treatment IP degree of protection Ordering and shipping details Category	TC IP66	
Light source Operating mode Environment Protective treatment IP degree of protection Ordering and shipping details Category Discount Schedule	TC IP66 21429 - 9001 SK,SKY	
Light source Operating mode Environment Protective treatment IP degree of protection Ordering and shipping details Category Discount Schedule GTIN	Push-to-test TC IP66 21429 - 9001 SK,SKY CS1	
Light source Operating mode Environment Protective treatment IP degree of protection Ordering and shipping details Category Discount Schedule GTIN Nbr. of units in pkg.	Push-to-test TC IP66 21429 - 9001 SK,SKY CS1 00785901734840	
Light source Operating mode Environment Protective treatment IP degree of protection Ordering and shipping details Category Discount Schedule GTIN Nbr. of units in pkg. Package weight(Lbs)	Push-to-test TC IP66 21429 - 9001 SK,SKY CS1 00785901734840 1	
Light source Operating mode Environment Protective treatment IP degree of protection Ordering and shipping details Category Discount Schedule GTIN Nbr. of units in pkg. Package weight(Lbs) Returnability	Push-to-test TC IP66 21429 - 9001 SK,SKY CS1 00785901734840 1 0.27 lb(US) (0.12 kg)	
Light source Operating mode Environment Protective treatment IP degree of protection Ordering and shipping details Category Discount Schedule GTIN Nbr. of units in pkg. Package weight(Lbs) Returnability	Push-to-test TC IP66 21429 - 9001 SK,SKY CS1 00785901734840 1 0.27 lb(US) (0.12 kg) Yes	
Light source Operating mode Environment Protective treatment IP degree of protection Ordering and shipping details Category Discount Schedule	Push-to-test TC IP66 21429 - 9001 SK,SKY CS1 00785901734840 1 0.27 lb(US) (0.12 kg) Yes	

Packing Units

Package 1 Height	6.35 in (16.129 cm)	

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.





Package 1 width	2.50 in (6.350 cm)	
Package 1 Length	16.13 in (40.968 cm)	

Offer Sustainability

Green Premium product
REACh Declaration
Yes
Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Yes
Yes
Yes
China RoHS declaration
Product Environmental Profile
End of Life Information
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
----------	-----------