Product data sheet Characteristics

9065SEO12

Melting Alloy Overload Relay Size 3 Three Pole 86A 600VAC

Product availability: Non-Stock - Not normally stocked in distribution facility



Price*: 247.90 USD



Main

Range of product	Separate Mounting
Thermal overload type	Melting alloy

Complementary

Main Range of product Separate Mounting Thermal overload type Melting alloy Complementary NEMA size 3 Number of thermal units required 3 Mounting support Panel [Ue] rated operational voltage 600 V AC Maximum Height 5.59 in (142.1 mm) Maximum Width 5.31 in (134.9 mm) Maximum Depth 5.75 in (146.1 mm) Ordering and shipping details Category 21661 - 9065 A,C,F,G,S(NOT SS) Discount Schedule CP1 GTIN 00785901788522 Nbr. of units in pkg. 1 Package weight(Lbs) 3.42 lb(Us) (1.55 kg) Returnability No Country of origin MX Package 1 Height 6.40 in (16.256 cm) Package 1 Height 6.70 in (17.018 cm)			
Range of product Separate Mounting Thermal overload type Melting alloy Complementary Separate Mounting NEMA size 3 Mounting support Panel (Le) rated operational voltage 600 V AC Maximum Height 5.59 in (142.1 mm) Maximum Width 5.31 in (134.9 mm) Maximum Depth 5.75 in (146.1 mm) Ordering and shipping details Category Category 21661 - 9065 A,C,F,G,S(NOT SS) Discount Schedule CP1 GTIN 00785901788522 Nbr. of units in pkg. 1 Package weight(Lbs) 3.42 lb(US) (1.55 kg) Returnability No Country of origin MX Packing Units Package 1 Height 6.40 in (16.256 cm)		•	
Range of product Separate Mounting Thermal overload type Melting alloy Complementary NEMA size 3 Number of thermal units required 3 Mounting support Panel (Ue) rated operational voltage 600 V AC Maximum Height 5.59 in (142.1 mm) Maximum Width 5.31 in (134.9 mm) Maximum Depth 5.75 in (146.1 mm) Cordering and shipping details Category 21661 - 9065 A,C,F,G,S(NOT SS) Discount Schedule CP1 GTIN 00785901788522 Nbr. of units in pkg. 1 Package weight(Lbs) 3.42 lb(US) (1.55 kg) Returnability No Country of origin MX Packing Units Package I Height 6.40 in (16.256 cm)			
Range of product Separate Mounting Thermal overload type Melting alloy Complementary Separate Mounting Separate Mounti			
Range of product Separate Mounting Thermal overload type Melting alloy Complementary NEMA size 3 Number of thermal units required 3 Mounting support Panel (Le) rated operational voltage 600 V AC Maximum Height 5.59 in (142.1 mm) Maximum Width 5.31 in (134.9 mm) Maximum Depth 5.75 in (146.1 mm) Ordering and shipping details Category Category 21661 - 9065 A,C,F,G,S(NOT SS) Discount Schedule CP1 GTIN 00785901788522 Nbr. of units in pkg. 1 Package weight(Lbs) 3.42 lb(US) (1.55 kg) Returnability No Country of origin MX Packing Units Package 1 Height 6.40 in (16.256 cm)			
Thermal overload type Melting alloy Complementary NEMA size 3 Number of thermal units required 3 Mounting support Panel [Ue] rated operational voltage 600 V AC Maximum Height 5.59 in (142.1 mm) Maximum Width 5.31 in (134.9 mm) Maximum Depth 5.75 in (146.1 mm) Ordering and shipping details Category 21661 - 9065 A,C.F.G,S(NOT SS) Discount Schedule CP1 GTIN 00785901788522 Nbr. of units in pkg. 1 Package weight(Lbs) 3.42 lb(US) (1.55 kg) Returnability No Country of origin MX Packing Units Package 1 Height 6.40 in (16.256 cm)			
Complementary NEMA size 3 Number of thermal units required 3 Mounting support Panel [Ue] rated operational voltage 600 V AC Maximum Height 5.59 in (142.1 mm) Maximum Width 5.31 in (134.9 mm) Maximum Depth 5.75 in (146.1 mm) Ordering and shipping details Category 21661 - 9065 A,C,F,G,S(NOT SS) Discount Schedule CP1 GTIN 00785901788522 Nbr. of units in pkg. 1 Package weight(Lbs) 3.42 lb(US) (1.55 kg) Returnability No Country of origin MX			
NEMA size 3 Number of thermal units required 3 Mounting support Panel [Ue] rated operational voltage 600 V AC Maximum Height 5.59 in (142.1 mm) Maximum Width 5.31 in (134.9 mm) Maximum Depth 5.75 in (146.1 mm) Ordering and shipping details Category 21661 - 9065 A,C,F,G,S(NOT SS) Discount Schedule CP1 GTIN 00785901788522 Nbr. of units in pkg. 1 Package weight(Lbs) 3.42 lb(US) (1.55 kg) Returnability No Country of origin MX Packing Units Package 1 Height 6.40 in (16.256 cm)	Thermal overload type	Melting alloy	
NEMA size 3 Number of thermal units required 3 Mounting support Panel [Ue] rated operational voltage 600 V AC Maximum Height 5.59 in (142.1 mm) Maximum Width 5.31 in (134.9 mm) Maximum Depth 5.75 in (146.1 mm) Ordering and shipping details Category 21661 - 9065 A,C,F,G,S(NOT SS) Discount Schedule CP1 GTIN 00785901788522 Nbr. of units in pkg. 1 Package weight(Lbs) 3.42 lb(US) (1.55 kg) Returnability No Country of origin MX Packing Units Package 1 Height 6.40 in (16.256 cm)			
NEMA size 3 Number of thermal units required 3 Mounting support Panel [Ue] rated operational voltage 600 V AC Maximum Height 5.59 in (142.1 mm) Maximum Width 5.31 in (134.9 mm) Maximum Depth 5.75 in (146.1 mm) Ordering and shipping details Category 21661 - 9065 A,C,F,G,S(NOT SS) Discount Schedule CP1 GTIN 00785901788522 Nbr. of units in pkg. 1 Package weight(Lbs) 3.42 lb(US) (1.55 kg) Returnability No Country of origin MX Packing Units Package 1 Height 6.40 in (16.256 cm)	Complementary		
Mounting support Panel [Ue] rated operational voltage 600 V AC Maximum Height 5.59 in (142.1 mm) Maximum Width 5.31 in (134.9 mm) Maximum Depth 5.75 in (146.1 mm) Ordering and shipping details Category 21661 - 9065 A,C,F,G,S(NOT SS) Discount Schedule CP1 GTIN 00785901788522 Nbr. of units in pkg. 1 Package weight(Lbs) 3.42 lb(US) (1.55 kg) Returnability No Country of origin MX Packing Units Package 1 Height 6.40 in (16.256 cm)		3	
[Ue] rated operational voltage 600 V AC Maximum Height 5.59 in (142.1 mm) Maximum Width 5.31 in (134.9 mm) Maximum Depth 5.75 in (146.1 mm) Ordering and shipping details Category 21661 - 9065 A,C,F,G,S(NOT SS) Discount Schedule CP1 GTIN 00785901788522 Nbr. of units in pkg. 1 Package weight(Lbs) 3.42 lb(US) (1.55 kg) Returnability No Country of origin MX Packing Units Package 1 Height 6.40 in (16.256 cm)	Number of thermal units required	3	
Maximum Height 5.59 in (142.1 mm) Maximum Width 5.31 in (134.9 mm) Maximum Depth 5.75 in (146.1 mm) Ordering and shipping details Category 21661 - 9065 A,C,F,G,S(NOT SS) Discount Schedule CP1 GTIN 00785901788522 Nbr. of units in pkg. 1 Package weight(Lbs) 3.42 lb(US) (1.55 kg) Returnability No Country of origin MX Packing Units Package 1 Height 6.40 in (16.256 cm)	Mounting support	Panel	
Maximum Width 5.31 in (134.9 mm) Maximum Depth 5.75 in (146.1 mm) Ordering and shipping details Category 21661 - 9065 A,C,F,G,S(NOT SS) Discount Schedule CP1 GTIN 00785901788522 Nbr. of units in pkg. 1 Package weight(Lbs) 3.42 lb(US) (1.55 kg) Returnability No Country of origin MX Packing Units Package 1 Height 6.40 in (16.256 cm)	[Ue] rated operational voltage	600 V AC	
Maximum Depth 5.75 in (146.1 mm) Ordering and shipping details Category 21661 - 9065 A,C,F,G,S(NOT SS) Discount Schedule CP1 GTIN 00785901788522 Nbr. of units in pkg. 1 Package weight(Lbs) 3.42 lb(US) (1.55 kg) Returnability No Country of origin MX Packing Units Package 1 Height 6.40 in (16.256 cm)	Maximum Height	5.59 in (142.1 mm)	
Ordering and shipping details Category 21661 - 9065 A,C,F,G,S(NOT SS) Discount Schedule CP1 GTIN 00785901788522 Nbr. of units in pkg. 1 Package weight(Lbs) 3.42 lb(US) (1.55 kg) Returnability No Country of origin MX Packing Units Package 1 Height 6.40 in (16.256 cm)	Maximum Width	5.31 in (134.9 mm)	
Category 21661 - 9065 A,C,F,G,S(NOT SS) Discount Schedule CP1 GTIN 00785901788522 Nbr. of units in pkg. 1 Package weight(Lbs) 3.42 lb(US) (1.55 kg) Returnability No Country of origin MX Packing Units Package 1 Height 6.40 in (16.256 cm)	Maximum Depth	5.75 in (146.1 mm)	
Category 21661 - 9065 A,C,F,G,S(NOT SS) Discount Schedule CP1 GTIN 00785901788522 Nbr. of units in pkg. 1 Package weight(Lbs) 3.42 lb(US) (1.55 kg) Returnability No Country of origin MX Packing Units Package 1 Height 6.40 in (16.256 cm)			
Category 21661 - 9065 A,C,F,G,S(NOT SS) Discount Schedule CP1 GTIN 00785901788522 Nbr. of units in pkg. 1 Package weight(Lbs) 3.42 lb(US) (1.55 kg) Returnability No Country of origin MX Packing Units Package 1 Height 6.40 in (16.256 cm)	Ordering and shipping details		
Discount Schedule CP1 GTIN 00785901788522 Nbr. of units in pkg. 1 Package weight(Lbs) 3.42 lb(US) (1.55 kg) Returnability No Country of origin MX Packing Units Package 1 Height 6.40 in (16.256 cm)		21661 - 9065 A.C.F.G.S(NOT SS)	
GTIN 00785901788522 Nbr. of units in pkg. 1 Package weight(Lbs) 3.42 lb(US) (1.55 kg) Returnability No Country of origin MX Packing Units Package 1 Height 6.40 in (16.256 cm)		600 800 80 80 80 80 M	
Nbr. of units in pkg. 1 Package weight(Lbs) 3.42 lb(US) (1.55 kg) Returnability No Country of origin MX Packing Units Package 1 Height 6.40 in (16.256 cm)			
Package weight(Lbs) 3.42 lb(US) (1.55 kg) Returnability No Country of origin MX Packing Units Package 1 Height 6.40 in (16.256 cm)	WC IN ARE IN		
Returnability No Country of origin MX Packing Units Package 1 Height 6.40 in (16.256 cm)	, 90 kG	3.42 lb(US) (1.55 kg)	
Country of origin MX Packing Units Package 1 Height 6.40 in (16.256 cm)			
Packing Units Package 1 Height 6.40 in (16.256 cm)	· · · · · · · · · · · · · · · · · · ·	MX	
Package 1 Height 6.40 in (16.256 cm)			
Package 1 Height 6.40 in (16.256 cm)	Packing Units		
		6.40 in (16.256 cm)	

Ordering and shipping details

Category	21661 - 9065 A,C,F,G,S(NOT SS)	, and a second s
Discount Schedule	CP1	
GTIN	00785901788522	<u> </u>
Nbr. of units in pkg.	1	o a
Package weight(Lbs)	3.42 lb(US) (1.55 kg)	
Returnability	No	
Country of origin	MX	<u> </u>

Packing Units

Package 1 Height	6.40 in (16.256 cm)	
Package 1 width	6.70 in (17.018 cm)	

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Oct 5, 2020

Package 1 Length	8.40 in (21.336 cm)	
Offer Sustainability		
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov	
EU RoHS Directive	Not compliant	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.	
Contractual warranty		
Warranty	18 months	