Product data sheet Characteristics

9065SEO5

Melting alloy overload relay, NEMA Size 1, three pole, 25 A, 600 VAC

Product availability: Stock - Normally stocked in distribution facility



Price*: 131.60 USD



Main

Range of product	Separate Mounting	
Thermal overload type	Melting alloy	

Complementary

NEMA size	1
Number of thermal units required	3
Mounting support	Panel
[Ue] rated operational voltage	600 V AC
Maximum Height	3.31 in (84.1 mm)
Maximum Width	3.53 in (89.7 mm)
Maximum Depth	3.97 in (100.8 mm)

Ordering and shipping details

Complementary NEMA size 1 Number of thermal units required 3 Mounting support Panel [Ue] rated operational voltage 600 V AC Maximum Height 3.31 in (84.1 mm) Maximum Width 3.53 in (89.7 mm) Maximum Depth 3.97 in (100.8 mm) Ordering and shipping details Category Category 21661 - 9065 A,C,F,G,S(NOT SS) Discount Schedule CP1 GTIN 00785901878827 Nbr. of units in pkg. 1 Package weight(Lbs) 1.02 lb(US) (0.46 kg) Returnability Yes Country of origin MX		Separate Mounting
Range of product Separate Mounting Thermal overload type Melting alloy Complementary NEMA size 1 Number of thermal units required 3 Mounting support Panel (Ue) rated operational voltage Maximum Height 3.31 in (84.1 mm) Maximum Width 3.53 in (89.7 mm) Maximum Depth 3.97 in (100.8 mm) Cordering and shipping details Category 21661 - 9065 A,C,F,G,S(NOT SS) Discount Schedule GTIN 00785901878827 Nbr. of units in pkg. 1 Package weight(Lbs) 1.02 lb(US) (0.46 kg) Returnability Yes Country of origin MX Package 1 Height 4.60 in (11.684 cm)	MARTINE .	Separate Mounting
Range of product Separate Mounting Thermal overload type Melting alloy Complementary NEMA size 1 Number of thermal units required 3 Mounting support Panel (Uel rated operational voltage 600 V AC Maximum Height 3.31 in (84.1 mm) Maximum Width 3.53 in (89.7 mm) Maximum Depth 3.97 in (100.8 mm) Cordering and shipping details Category 21661 - 9065 A,C,F,G,S(NOT SS) Discount Schedule CP1 GTIN 00785901878827 Nbr. of units in pkg. 1 Package weight(Lbs) 1.02 lb(US) (0.46 kg) Returnability Yes Country of origin MX Packing Units Package 1 Height 4.60 in (11.684 cm)		Separate Mounting
Range of product Thermal overload type Melting alloy Complementary NEMA size 1 Number of thermal units required 3 Mounting support Panel [Ue] rated operational voltage 600 V AC Maximum Height 3.31 in (84.1 mm) Maximum Width 3.53 in (89.7 mm) Maximum Depth 3.97 in (100.8 mm) Cordering and shipping details Category 21661 - 9065 A,C,F,G,S(NOT SS) Discount Schedule GTIN 00785901878827 Nbr. of units in pkg. 1 Package weight(Lbs) 1.02 lb(Us) (0.46 kg) Returnability Yes Country of origin MX Packing Units Package 1 Height 4.60 in (11.684 cm)		Senarate Mounting
Range of product Thermal overload type Melting alloy Complementary NEMA size 1 Number of thermal units required 3 Mounting support Panel [Ue] rated operational voltage 600 V AC Maximum Height 3.31 in (84.1 mm) Maximum Width 3.53 in (89.7 mm) Maximum Depth 3.97 in (100.8 mm) Cordering and shipping details Category 21661 - 9065 A,C,F,G,S(NOT SS) Discount Schedule GTIN 00785901878827 Nbr. of units in pkg. 1 Package weight(Lbs) 1.02 lb(Us) (0.46 kg) Returnability Yes Country of origin MX Packing Units Package 1 Height 4.60 in (11.684 cm)		Separate Mounting
Range of product Separate Mounting Thermal overload type Melting alloy Complementary		Senarate Mounting
Complementary NEMA size 1 Number of thermal units required 3 Mounting support Panel [Ue] rated operational voltage 600 V AC Maximum Height 3.31 in (84.1 mm) Maximum Width 3.53 in (89.7 mm) Maximum Depth 3.97 in (100.8 mm) Ordering and shipping details Category Category 21661 - 9065 A,C,F,G,S(NOT SS) Discount Schedule CP1 GTIN 00785901878827 Nbr. of units in pkg. 1 Package weight(Lbs) 1.02 lb(US) (0.46 kg) Returnability Yes Country of origin MX	range of product	Ocparate Modifiling
NEMA size 1 Number of thermal units required 3 Mounting support Panel [Ue] rated operational voltage 600 V AC Maximum Height 3.31 in (84.1 mm) Maximum Width 3.53 in (89.7 mm) Maximum Depth 3.97 in (100.8 mm) Ordering and shipping details Category 21661 - 9065 A,C,F,G,S(NOT SS) Discount Schedule CP1 GTIN 00785901878827 Nbr. of units in pkg. 1 Package weight(Lbs) 1.02 lb(US) (0.46 kg) Returnability Yes Country of origin MX Packing Units Package 1 Height 4.60 in (11.684 cm)	Thermal overload type	Melting alloy
Number of thermal units required 3 Mounting support Panel [Ue] rated operational voltage 600 V AC Maximum Height 3.31 in (84.1 mm) Maximum Width 3.53 in (89.7 mm) Maximum Depth 3.97 in (100.8 mm) Ordering and shipping details Category 21661 - 9065 A,C,F,G,S(NOT SS) Discount Schedule CP1 GTIN 00785901878827 Nbr. of units in pkg. 1 Package weight(Lbs) 1.02 lb(US) (0.46 kg) Returnability Yes Country of origin MX Packing Units Package 1 Height 4.60 in (11.684 cm)		
NEMA size 1 Number of thermal units required 3 Mounting support Panel [Ue] rated operational voltage 600 V AC Maximum Height 3.31 in (84.1 mm) Maximum Width 3.53 in (89.7 mm) Maximum Depth 3.97 in (100.8 mm) Ordering and shipping details Category Category 21661 - 9065 A,C,F,G,S(NOT SS) Discount Schedule CP1 GTIN 00785901878827 Nbr. of units in pkg. 1 Package weight(Lbs) 1.02 lb(US) (0.46 kg) Returnability Yes Country of origin MX Packing Units Package 1 Height 4.60 in (11.684 cm)	Complementary	
Mounting support Panel [Ue] rated operational voltage 600 V AC Maximum Height 3.31 in (84.1 mm) Maximum Width 3.53 in (89.7 mm) Maximum Depth 3.97 in (100.8 mm) Ordering and shipping details Category 21661 - 9065 A,C,F,G,S(NOT SS) Discount Schedule CP1 GTIN 00785901878827 Nbr. of units in pkg. 1 Package weight(Lbs) 1.02 lb(US) (0.46 kg) Returnability Yes Country of origin MX Packing Units Package 1 Height 4.60 in (11.684 cm)		1
[Ue] rated operational voltage 600 V AC Maximum Height 3.31 in (84.1 mm) Maximum Width 3.53 in (89.7 mm) Maximum Depth 3.97 in (100.8 mm) Ordering and shipping details Category 21661 - 9065 A,C,F,G,S(NOT SS) Discount Schedule CP1 GTIN 00785901878827 Nbr. of units in pkg. 1 Package weight(Lbs) 1.02 lb(US) (0.46 kg) Returnability Yes Country of origin MX Packing Units Package 1 Height 4.60 in (11.684 cm)	Number of thermal units required	3
Maximum Height 3.31 in (84.1 mm) Maximum Width 3.53 in (89.7 mm) Maximum Depth 3.97 in (100.8 mm) Ordering and shipping details Category 21661 - 9065 A,C,F,G,S(NOT SS) Discount Schedule CP1 GTIN 00785901878827 Nbr. of units in pkg. 1 Package weight(Lbs) 1.02 lb(US) (0.46 kg) Returnability Yes Country of origin MX	Mounting support	Panel
Maximum Width 3.53 in (89.7 mm) Maximum Depth 3.97 in (100.8 mm) Ordering and shipping details Category 21661 - 9065 A,C,F,G,S(NOT SS) Discount Schedule CP1 GTIN 00785901878827 Nbr. of units in pkg. 1 Package weight(Lbs) 1.02 lb(US) (0.46 kg) Returnability Yes Country of origin MX	[Ue] rated operational voltage	600 V AC
Maximum Depth 3.97 in (100.8 mm) Ordering and shipping details Category 21661 - 9065 A,C,F,G,S(NOT SS) Discount Schedule CP1 GTIN 00785901878827 Nbr. of units in pkg. 1 Package weight(Lbs) 1.02 lb(US) (0.46 kg) Returnability Yes Country of origin MX Packing Units Package 1 Height 4.60 in (11.684 cm)	Maximum Height	3.31 in (84.1 mm)
Ordering and shipping details Category 21661 - 9065 A,C,F,G,S(NOT SS) Discount Schedule CP1 GTIN 00785901878827 Nbr. of units in pkg. 1 Package weight(Lbs) 1.02 lb(US) (0.46 kg) Returnability Yes Country of origin MX Packing Units Package 1 Height 4.60 in (11.684 cm)	Maximum Width	3.53 in (89.7 mm)
Category 21661 - 9065 A,C,F,G,S(NOT SS) Discount Schedule CP1 GTIN 00785901878827 Nbr. of units in pkg. 1 Package weight(Lbs) 1.02 lb(US) (0.46 kg) Returnability Yes Country of origin MX Packing Units Package 1 Height 4.60 in (11.684 cm)	Maximum Depth	3.97 in (100.8 mm)
Discount Schedule CP1 GTIN 00785901878827 Nbr. of units in pkg. 1 Package weight(Lbs) 1.02 lb(US) (0.46 kg) Returnability Yes Country of origin MX Packing Units Package 1 Height 4.60 in (11.684 cm)		
Category 21661 - 9065 A,C,F,G,S(NOT SS) Discount Schedule CP1 GTIN 00785901878827 Nbr. of units in pkg. 1 Package weight(Lbs) 1.02 lb(US) (0.46 kg) Returnability Yes Country of origin MX Packing Units Package 1 Height 4.60 in (11.684 cm)	Ordering and shipping details	
GTIN 00785901878827 Nbr. of units in pkg. 1 Package weight(Lbs) 1.02 lb(US) (0.46 kg) Returnability Yes Country of origin MX Packing Units Package 1 Height 4.60 in (11.684 cm)		21661 - 9065 A,C,F,G,S(NOT SS)
Nbr. of units in pkg. 1 Package weight(Lbs) 1.02 lb(US) (0.46 kg) Returnability Yes Country of origin MX Packing Units Package 1 Height 4.60 in (11.684 cm)	Discount Schedule	CP1
Package weight(Lbs) 1.02 lb(US) (0.46 kg) Returnability Yes Country of origin MX Packing Units Package 1 Height 4.60 in (11.684 cm)	GTIN	00785901878827
Returnability Yes Country of origin MX Packing Units Package 1 Height 4.60 in (11.684 cm)	Nbr. of units in pkg.	1
Country of origin MX Packing Units Package 1 Height 4.60 in (11.684 cm)	Package weight(Lbs)	1.02 lb(US) (0.46 kg)
Packing Units Package 1 Height 4.60 in (11.684 cm)	Returnability	Yes
Package 1 Height 4.60 in (11.684 cm)	Country of origin	MX
Package 1 Height 4.60 in (11.684 cm)		
Package 1 Height 4.60 in (11.684 cm)	Packing Units	
Package 1 width 5.30 in (13.462 cm)		4.60 in (11.684 cm)
	Package 1 width	5.30 in (13.462 cm)

Packing Units

Package 1 Height	4.60 in (11.684 cm)	
Package 1 width	5.30 in (13.462 cm)	F

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Oct 5, 2020

Package 1 Length	5.50 in (13.970 cm)	
Offer Sustainability		
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov	
EU RoHS Directive	Not compliant	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.	
Contractual warranty		
Warranty	18 months	